

# AURA 2x2

RECESSED

QuickShip+



The perfect blend of lighting performance and timeless aesthetic. Aura features a triple lens design with a ribbed center optical diffuser that provides balanced brightness and visual comfort. High-performance LED technology combined with the flexibility of optional integral controls deliver considerable energy savings. Aura is ideal for a variety of indoor applications including offices, institutions and commercial spaces. Installation and maintenance are made easy with toolless lens installation and access to all components from below.



Depletion Policy - 50 units

14 calendar days or less

## Ordering Guide

PRODUCT ID		SIZE		NOMINAL LUMENS		CRI		COLOUR TEMP.		SHIELDING		FINISH	
<b>AULED</b>	Aura	<b>22</b>	2'X2'	<b>2500</b>	2500 lm	<b>80</b>	80 CRI	<b>30</b>	3000 K	<b>SO</b>	spotless optics	<b>W</b>	white
				<b>3000</b>	3000 lm			<b>35</b>	3500 K				
				<b>4000</b>	4000 lm								
				<b>4400</b>	4400 lm								

VOLTAGE		DRIVER		CIRCUITS		MOUNTING		BATTERY (OPTIONAL)		OTHER (OPTIONAL)	
<b>120</b>	120 V	<b>DP</b>	dimming (0-10V) 1%	<b>1</b>	1 circuit	<b>TB9</b>	t-bar 9/16"	<b>B#</b>	battery pack	<b>F</b>	fuse <sup>(4)</sup>
<b>277</b>	277 V	<b>D</b>	dimming (0-10V) 5% 347V standard <sup>(2)</sup>			<b>TB15</b>	t-bar 15/16"			<b>FW(#)</b>	flex whip (6' std)
<b>347</b>	347 V <sup>(1)</sup>	<b>LT</b>	Lutron <sup>(3)</sup>			<b>ST</b>	screw slot t-bar			<b>CP</b>	Chicago plenum
<b>UNV</b>	universal					<b>TG9</b>	tegular 9/16"				
						<b>TG15</b>	tegular 15/16"				
						<b>DF</b>	drywall flange				
(1) D dimming (0-10V) 5% standard		(2) For 347V only (3) Hi-Lume A Series L3D						Please consult factory		(4) Requires 120V or 277V	



Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.

Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.