



Beam4 LED: for a clean, uniform, continuous end-to-end luminous effect from a best-selling pendant linear luminaire that naturally compliments any architectural design with minimal intrusion. Great for shallow ceiling spaces and available with multiple lengths and lumen packages to provide the right amount of light for the allowed wattage.



Depletion Policy - 200 Feet

14 calendar days or less

Ordering Guide

PRODUCT ID	NOM. LUMENS/FT	CRI	COLOR TEMP.	SHIELDING	LENGTH
BBDLED BEAM4 Pendant LED	400 400 lm/ft	80 80 CRI	30 3000 K	SO spotless lens	2 2'
	500 500 lm/ft		35 3500 K		4 4'
	750 750 lm/ft				6 6'
	1000 1000 lm/ft				8 8'
					10 10'
					12 12'
					S# System Run ⁽¹⁾
Constul factory for other lumen packages				Use spotless lens	(1) 4' increments only

FINISH	VOLTAGE	DRIVER	CIRCUITS	MOUNTING	BATTERY (OPTIONAL)	OTHER (OPTIONAL)
W white	120 120 V	DP dimming (0-10V) 1%	1 1 circuit	CA(#) drywall+cable length (36" std.)	B# battery pack 4' sections	F fuse
AP aluminum paint	277 277 V	D dimming (0-10V) 5% 347V standard ⁽²⁾		CT9(#) TB/TG 9/16+cable length (36" std.)		
	347 347 V ⁽¹⁾	LT Lutron ⁽³⁾		CT15(#) TB/TG 15/16+cable length (36" std.)		
	UNV universal					
	(1) D dimming (0-10V) 5% standard	(2) For 347V only (3) Hi-Lume A Series L3D		See Ceiling Mount Guide for more details	Please consult factory	Requires 120V or 277V



Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+. Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.