


Beam4 LED: for a clean, uniform, continuous end-to-end luminous effect from a best-selling recessed linear luminaire that naturally compliments any architectural design with minimal intrusion. Great for shallow ceiling spaces and available with multiple lengths and lumen packages to provide the right amount of light for the allowed wattage.



Flush lens shown



Depletion Policy - 200 Feet

14 calendar days or less

Ordering Guide

PRODUCT ID	NOM. LUMENS/FT	CRI	COLOR TEMP.	SHIELDING	LENGTH
BBRLED BEAM4 Recessed LED	400 400 lm/ft	80 80 CRI	30 3000 K	FL flush RG regressed	4 4'
	500 500 lm/ft		35 3500 K		6 6'
	750 750 lm/ft				8 8'
	1000 1000 lm/ft				12 12'
					S# System Run ⁽¹⁾
				All lens options use spotless lens	(1) 4' increments only

FINISH	VOLTAGE	DRIVER	CIRCUITS	MOUNTING	BATTERY (OPTIONAL)	OTHER (OPTIONAL)
W white	120 120 V 277 277 V 347 347 V ⁽²⁾ UNV universal	DP dimming (0-10V) 1% D dimming (0-10V) 5% 347V standard ⁽³⁾ LT Lutron ⁽⁴⁾	1 1 circuit	TB9 t-bar 9/16" TB15 t-bar 15/16" ST screw slot t-bar TG9 tegular 9/16" TG15 tegular 15/16" DF drywall flange DS drywall spackle flange	B# battery pack 4' sections	EF end feed FW(#) flex whip (6' std) CP Chicago plenum HD hold down clip F Fuse ⁽⁴⁾
	⁽²⁾ D dimming (0-10V) 5% standard	⁽³⁾ For 347V only ⁽⁴⁾ HI-Lume A Series L3D			Please consult factory	⁽⁴⁾ Requires 120V or 277V

1 Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+. Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.