



Beam4 LED: for a clean, uniform, continuous end-to-end luminous effect from a best-selling recessed linear luminaire that naturally compliments any architectural design with minimal intrusion. Great for shallow ceiling spaces and available with multiple lengths and lumen packages to provide the right amount of light for the allowed wattage.




Depletion Policy - 200 Feet

14 calendar days or less

Ordering Guide

PRODUCT ID		NOM. LUMENS/FT		CRI		COLOR TEMP.		SHIELDING		LENGTH	
BBSLED	BEAM4 Surface LED	400	400 lm/ft	80	80 CRI	30	3000 K	SO	spotless lens	2	2'
		500	500 lm/ft							4	4'
		750	750 lm/ft							6	6'
		1000	1000 lm/ft							8	8'
										10	10'
				12	12'			S#	System Run ⁽¹⁾		
								Use spotless lens		(1) 4' increments only	

FINISH		VOLTAGE		DRIVER		CIRCUITS		MOUNTING		BATTERY (OPTIONAL)		OTHER (OPTIONAL)					
W	white	120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	S	surface drywall ceiling	B#	battery pack 4' sections	F	fuse				
		277	277 V											D	dimming (0-10V) 5% 347V standard ⁽³⁾	FW#	flex whip (6' std)
		347	347 V ⁽²⁾														
		UNV	universal														
(2) D dimming (0-10V) 5% standard		(3) For 347V only				Please consult factory		Requires 120V or 277V									
		(4) HI-Lume A Series L3D															

 **1** Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+. Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.