



Beam6 LED is a compact, linear system with multiple lighting, mounting, and design options, suitable for large spaces and high ceilings. It delivers efficient direct light distributions, with optional MR16 accents. IC Controls equip a BEAM 6 LED system to reduce energy consumption further still.




Depletion Policy - 200 Feet

14 calendar days or less

Ordering Guide

PRODUCT ID		NOM. LUMENS/FT		CRI		COLOR TEMP.		SHIELDING		LENGTH		
B6DLED	BEAM6 Pendant LED	400	400 lm/ft	80	80 CRI	30	3000 K	SO	spotless lens	2	2'	
		500	500 lm/ft				35			3500 K	4	4'
		750	750 lm/ft								6	6'
		1000	1000 lm/ft								8	8'
										10	10'	
										12	12'	
										S#	System Run ⁽¹⁾	
								Use spotless lens		(1) 4' increments only		

FINISH		VOLTAGE		DRIVER		CIRCUITS		MOUNTING		BATTERY (OPTIONAL)		OTHER (OPTIONAL)	
W	white	120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	CA(#)	drywall+cable length (36" std.)	B#	battery pack 4' sections	F	fuse
AP	aluminum paint	277	277 V	D	dimming (0-10V) 5% 347V standard ⁽²⁾			CT9(#)	TB/TG 9/16+cable length (36" std.)				
		347	347 V ⁽¹⁾	LT	Lutron ⁽³⁾			CT15(#)	TB/TG 15/16+cable length (36" std.)				
		UNV	universal										
		(1) D dimming (0-10V) 5% standard		(2) For 347V only (3) Hi-Lume A Series L3D				See Ceiling Mount Guide for more details		Please consult factory		Requires 120V or 277V	

 **1** Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+. Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.