



This compact, efficient extruded aluminum linear pendant with trim helps create visually comfortable spaces with a subtle glow. Versatile and classic, will fit many applications to provide a good ambient light layer as well as vertical illumination from a primarily direct source.



Depletion Policy - 200 Feet

14 calendar days or less

Ordering Guide

PRODUCT ID		NOMINAL LUMENS/FT		CRI		COLOR TEMPERATURE		SHIELDING		LENGTH/FT	
MBLED	Mini Box Pendant LED	500	500 lm/ft	80	80 CRI	30	3000 K	S	satin lens	2	2'
		600	600 lm/ft			35	3500 K			4	4'
		800	800 lm/ft							8	8'
		1000	1000 lm/ft							12	12'
										16	16'
						20	20'			24	24'
		Consult factory for other lumen packages									

FINISH		VOLTAGE		DRIVER		CIRCUITS		MOUNTING/SUSPENSION		BATTERY (OPTIONAL)		OTHER (OPTIONAL)	
W	white	120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	CA(#)	drywall+cable length (36" std.)	B#	battery pack 4' sections	F	fuse
AP	aluminum paint	277	277 V	D	dimming (0-10V) 5% 347V standard ⁽²⁾			CT9(#)	TB/TG 9/16+cable length (36" std.)				
		347	347 V ⁽¹⁾	LT	Lutron ⁽³⁾			CT15(#)	TB/TG 15/16+cable length (36" std.)				
		UNV	universal										
		(1) D dimming (0-10V) 5%		(2) For 347V only (3) Hi-Lume A Series L3D				See Ceiling Mount Guide for more details		Specify quantity Please consult factory		Requires 120V or 277V	



Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.

Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.