



This compact, efficient extruded aluminum linear pendant with trim helps create visually comfortable spaces with a subtle glow. Versatile and classic, will fit many applications to provide a good ambient light layer as well as vertical illumination from a primarily direct source.



Depletion Policy - 200 Feet

14 calendar days or less

Ordering Guide

PRODUCT ID		NOMINAL LUMENS/FT		CRI		COLOR TEMPERATURE		SHIELDING		LENGTH/FT	
MBSLED	Mini Box Surface LED	500	500 lm/ft	80	80 CRI	30	3000 K	S	satin lens	2	2'
		600	600 lm/ft				4			4'	
		800	800 lm/ft				8			8'	
		1000	1000 lm/ft				12			12'	
							16			16'	
				20	20'						
				24	24'						

FINISH		VOLTAGE		DRIVER		CIRCUITS		MOUNTING/SUSPENSION		BATTERY (OPTIONAL)		OTHER (OPTIONAL)					
W	white	120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	S	surface drywall ceiling	B#	battery pack 4' sections	F	fuse				
		277	277 V											D	dimming (0-10V) 5% 347V standard ⁽²⁾	FW#	flex whip (6' std)
		347	347 V ⁽¹⁾														
		UNV	universal														
(1) D dimming (0-10V) 5% standard		(2) For 347V only		(3) Hi-Lume A Series L3D		Specify quantity Please consult factory		Requires 120V or 277V									



Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+. Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.