



**DIA LED** troffers are high performance recessed luminaires that deliver soft ambient light via a patented VL Optic™. Light is transmitted through a luminous lens without harsh contrast. The precision center refractor and translucent side panels offer a balanced aesthetic. Best used when high efficiency and visual comfort are key.



\*Check the latest update on the DLC website for complete information. Not all versions may be DLC qualified.



cULus Listed Type I.C.



Depletion Policy - 50 units

14 calendar days or less

### Ordering Guide

PRODUCT ID		SIZE	NOMINAL LUMENS		CRI		COLOUR TEMP.		SHIELDING		FINISH	
<b>DIALED</b>	Dia LED	<b>22</b> 2'X2'	<b>2500</b>	2500 lm	<b>80</b>	80 CRI	<b>30</b>	3000 K	<b>VL</b>	VL optics	<b>W</b>	white
			<b>3000</b>	3000 lm			<b>35</b>	3500 K				
			<b>4000</b>	4000 lm								
			<b>4400</b>	4400 lm								

VOLTAGE		DRIVER	CIRCUITS		MOUNTING		BATTERY (OPTIONAL)		OTHER (OPTIONAL)	
<b>120</b>	120 V	<b>DP</b> dimming (0-10V) 1%	<b>1</b>	1 circuit	<b>TB9</b>	t-bar 9/16"	<b>B#</b>	battery pack	<b>F</b>	fuse <sup>(4)</sup>
<b>277</b>	277 V	<b>D</b> dimming (0-10V) 5% 347V standard <sup>(2)</sup>			<b>TB15</b>	t-bar 15/16"			<b>FW(#)</b>	flex whip (6' std)
<b>347</b>	347 V <sup>(1)</sup>	<b>LT</b> Lutron <sup>(3)</sup>			<b>ST</b>	screw slot t-bar			<b>CP</b>	Chicago plenum
<b>UNV</b>	universal				<b>TG9</b>	tegular 9/16"				
					<b>TG15</b>	tegular 15/16"				

(1) D dimming (0-10V) 5% standard      (2) For 347V only  
 (3) Hi-Lume A Series L3D      (4) Requires 120V or 277V



Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+. Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.