



Combining crisp lines and a clean, rounded design. **LT SurroundLite** brings high efficiency, glare control and flexible options ideal for illuminating medium and large spaces. Exclusive SurroundLite optics produce balanced brightness, sending wide planes of light in all directions.



*Check the latest update on the DLC website for complete information. Not all versions may be DLC qualified.



Depletion Policy - 200 Feet

14 calendar days or less

Ordering Guide

PRODUCT ID		LIGHT ENGINE		NOMINAL LUMENS/FT		CRI		COLOR TEMPERATURE		SHIELDING	
LTLED	LT SurroundLite Pendant LED	SL 80/20	SurroundLite 80% up/20% down	800	800 lm/ft	80	80 CRI	30	3000 K	SO	spotless lens
				1000	1000 lm/ft			35	3500 K	SR	satin ribbed lens
										PL	louver
				Consult factory for other lumen packages							

FIXTURE LENGTH		FINISH		VOLTAGE		DRIVER		CIRCUITS		MOUNTING/SUSPENSION		BATTERY (OPTIONAL)		OTHER(OPTIONAL)	
4	4'	W	white	120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	CA(#)	drywall+cable length (36" std.)	B#	battery pack (integral)	F	fuse
8	8'	AP	aluminum paint	277	277 V	D	dimming (0-10V) 5% 347V standard ⁽²⁾			CT9(#)	TB/TG 9/16+cable length (36" std.)				
12	12'			347	347 V ⁽¹⁾	LT	Lutron ⁽³⁾			CT15(#)	TB/TG 15/16+cable length (36" std.)				
16	16'			UNV	universal										
20	20'														
24	24'														
				(1) D dimming (0-10V) 5%		(2) For 347V only (3) Hi-Lume A Series L3D		See Ceiling Mount Guide for more details				For minimum 4' long fixture only		Requires 120V or 277V	

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.

Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.

July 2017

