



When all you need is a trace of light, **Sculpt** offers a 1.5" wide linear luminaire that departs from traditional linear footprints. Sculpt delivers the same quality of light and efficiency as larger profile products but in a clean, new, low profile look. Select from our range of lower lumen packages below to ensure balanced luminance and overall visual comfort.



Depletion Policy - 200 Feet

14 calendar days or less

### Ordering Guide

PRODUCT ID		NOM.LUMENS/FT UP		NOM.LUMENS/FT DOWN		CRI		COLOR TEMP.		SHIELDING		LINEAR LENGTH	
SCDI	Sculpt Pendant Direct/Indirect	300	300 lm/ft	300	300 lm/ft	80	80 CRI	30	3000 K	FL	flush	2	2'
		400	400 lm/ft	400	400 lm/ft			4	4'				
		500	500 lm/ft	500	500 lm/ft			8	8'				
								10	10'				
								12	12'				
												16	16'
												20	20'
												24	24'
		Please consult factory for other lumen packages		Please consult factory for other lumen packages		Applies to both UP & DOWN.		Applies to both UP & DOWN.		All lens options use spotless lens			

FINISH		VOLTAGE		DRIVER		CIRCUITS		MOUNTING/SUSPENSION		BATTERY (OPTIONAL)		OTHER	
W	white	120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	CA(#)	drywall+cable length (36" std.)	B#	battery pack	F	fuse <sup>(4)</sup>
AP	aluminum paint	277	277 V	D	dimming (0-10V) 5% 347V standard <sup>(2)</sup>			CT9(#)	TB/TG 9/16+cable length (36" std.)			FW(#)	flex whip (6' std)
		347	347 V <sup>(1)</sup>	LT	Lutron <sup>(3)</sup>			CT15(#)	TB/TG 15/16+cable length (36" std.)				
		(1) D dimming (0-10V) 5% standard		Applies to both UP & DOWN. (2) For 347V only (3) Hi-Lume A Series L3D		Control UP & DOWN lights together		<a href="#">See Ceiling Mount Guide for more details</a>		Please consult factory		(4) Requires 120V or 277V	



Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.

Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.