



When all you need is a trace of light, **Sculpt** offers a 1.5" wide linear luminaire that departs from traditional linear footprints. Sculpt delivers the same quality of light and efficiency as larger profile products but in a clean, new, low profile look. Select from our range of lower lumen packages below to ensure balanced luminance and overall visual comfort.



Depletion Policy - 200 Feet

14 calendar days or less

### Ordering Guide

PRODUCT ID		NOM. LUMENS/FT		CRI		COLOR TEMP.		SHIELDING		LINEAR LENGTH		FINISH		VOLTAGE			
<b>SCR</b>	Sculpt Recessed	<b>300</b>	300 lm/ft	<b>80</b>	80 CRI	<b>30</b>	3000 K	<b>FL</b>	flush	<b>2</b>	2'	<b>W</b>	white	<b>120</b>	120 V		
		<b>400</b>	400 lm/ft			<b>35</b>	3500 K			<b>4</b>	4'			<b>277</b>	277 V		
		<b>500</b>	500 lm/ft			<b>8</b>	8'			<b>347</b>	347 V						
		<b>12</b>	12'			<b>UNV</b>	universal <sup>(1)</sup>										
		<b>16</b>	16'			<b>20</b>	20'			<b>24</b>	24'						
Please consult factory for other lumen packages												All lens options use spotless lens				(1) D dimming (0-10V) 5% standard	

DRIVER		CIRCUITS		MOUNTING				BATTERY (OPTIONAL)		OTHER	
<b>DP</b>	dimming (0-10V) 1%	<b>1</b>	1 circuit	<b>MFTB9</b>	MiniFlange t-bar 9/16"	<b>ST</b>	screw slot t-bar	<b>B#</b>	battery pack	<b>F</b>	fuse <sup>(4)</sup>
<b>D</b>	dimming (0-10V) 5% 347V standard <sup>(2)</sup>			<b>MFTB15</b>	MiniFlange t-bar 15/16"	<b>TG9</b>	tegarular 9/16"			<b>FW(#)</b>	flex whip (6' std)
<b>LT</b>	Lutron <sup>(3)</sup>			<b>MFST</b>	MiniFlange screw slot t-bar	<b>TG15</b>	tegarular 15/16"			<b>CP</b>	Chicago plenum
				<b>MFTG9</b>	MiniFlange 9/16" t-tegarular	<b>DF</b>	drywall flange				
				<b>MFTG15</b>	MiniFlange 15/16" t-tegarular	<b>DS</b>	drywall spackle flange				
		<b>TB9</b>	t-bar 9/16"								
		<b>TB15</b>	t-bar 15/16"								
(2) For 347V only (3) Hi-Lume A Series L3D								Please consult factory		(4) Requires 120V or 277V	

