



When you're looking for a basic mid-size pendant that is powered by Axis Lighting's **SurroundLite** technology, **Slim** Pendant is a great choice. With its wide 360 degree uplight distribution, discover how you can eliminate luminaires or use shorter luminaires in your design without compromising light levels, light quality and visual comfort. You have to see it to believe it!



Depletion Policy - 200 Feet

**14 calendar days or less**

**Ordering Guide**

PRODUCT ID	LIGHT ENGINE	NOMINAL LUMENS/FT	CRI	COLOR TEMPERATURE	SHIELDING	SHIELDING LENGTH
<b>SLED</b> Slim SurroundLite Pendant LED	<b>SL 0/100</b> SurroundLite 0% up/100% down	<b>800</b> 800 lm/ft <b>1000</b> 1000 lm/ft	<b>80</b> 80 CRI	<b>30</b> 3000 K <b>35</b> 3500 K	<b>VL</b> VL optic <b>SM</b> smooth lens	<b>4</b> 4' <b>8</b> 8' <b>12</b> 12'
		Consult factory for other lumen packages				

FIXTURE LENGTH	FINISH	VOLTAGE	DRIVER	CIRCUITS	MOUNTING/SUSPENSION	BATTERY (OPTIONAL)	OTHER(OPTIONAL)
<b>4</b> 4' <b>8</b> 8' <b>12</b> 12' <b>16</b> 16' <b>20</b> 20' <b>24</b> 24'	<b>W</b> white <b>AP</b> aluminum paint	<b>120</b> 120 V <b>277</b> 277 V <b>347</b> 347 V <sup>(1)</sup> <b>UNV</b> universal	<b>DP</b> dimming (0-10V) 1% <b>D</b> dimming (0-10V) 5% 347V standard <sup>(2)</sup> <b>LT</b> Lutron <sup>(3)</sup>	<b>1</b> 1 circuit	<b>CA(#)</b> drywall+cable length (36" std.) <b>CT9(#)</b> TB/TG 9/16+cable length (36" std.) <b>CT15(#)</b> TB/TG 15/16+cable length (36" std.)	<b>B#</b> battery pack (integral)	<b>F</b> fuse
		(1) D dimming (0-10V) 5% standard	(2) For 347V only (3) Hi-Lume A Series L3D	<a href="#">See Ceiling Mount Guide for more details</a>		For minimum 4' long fixture only	Requires 120V or 277V

