



When you're looking for a basic mid-size pendant that is powered by Axis Lighting's **SurroundLite** technology, **Slim** Pendant is a great choice. With its wide 360 degree uplight distribution, discover how you can eliminate luminaires or use shorter luminaires in your design without compromising light levels, light quality and visual comfort. You have to see it to believe it!



Depletion Policy - 200 Feet

14 calendar days or less

Ordering Guide

PRODUCT ID		LIGHT ENGINE		NOMINAL LUMENS/FT		CRI		COLOR TEMPERATURE		SHIELDING		SHIELDING LENGTH	
SLLED	Slim SurroundLite Pendant LED	SL 25/75	SurroundLite 25% up/75% down	800	800 lm/ft	80	80 CRI	30	3000 K	VL	VL optic	4	4'
				1000	1000 lm/ft			35	3500 K	SM	smooth lens	8	8'
												12	12'
				Applies to both UP & DOWN. Consult factory for other lumen packages		Applies to both UP & DOWN.		Applies to both UP & DOWN.					

FIXTURE LENGTH		FINISH		VOLTAGE		DRIVER		CIRCUITS		MOUNTING/SUSPENSION		BATTERY (OPTIONAL)		OTHER (OPTIONAL)	
4	4'	W	white	120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	CA(#)	drywall+cable length (36" std.)	B#	battery pack (integral)	F	fuse
8	8'	AP	aluminum paint	277	277 V	D	dimming (0-10V) 5% 347V standard ⁽²⁾			CT9(#)	TB/TG 9/16+cable length (36" std.)				
12	12'			347	347 V ⁽¹⁾	LT	Lutron ⁽³⁾			CT15(#)	TB/TG 15/16+cable length (36" std.)				
16	16'			UNV	universal										
20	20'														
24	24'														
				(1) D dimming (0-10V) 5%		(2) For 347V only (3) Hi-Lume A Series L3D						For minimum 4' long fixture only		Requires 120V or 277V	

! Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+. Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.