



When you're looking for a basic mid-size pendant that is powered by Axis Lighting's **SurroundLite** technology, **Slim** Pendant is a great choice. With its wide 360 degree uplight distribution, discover how you can eliminate luminaires or use shorter luminaires in your design without compromising light levels, light quality and visual comfort. You have to see it to believe it!



Depletion Policy - 200 Feet

14 calendar days or less

Ordering Guide

PRODUCT ID	LIGHT ENGINE	NOMINAL LUMENS/FT	CRI	COLOR TEMPERATURE	SHIELDING	SHIELDING LENGTH
SLED Slim SurroundLite Pendant LED	SL 80/20 SurroundLite 80% up/20% down	800 800 lm/ft 1000 1000 lm/ft	80 80 CRI	30 3000 K 35 3500 K	VL VL optic SM smooth lens	4 4' 8 8' 12 12'
		Applies to both UP & DOWN. Consult factory for other lumen packages	Applies to both UP & DOWN.	Applies to both UP & DOWN.		

FIXTURE LENGTH	FINISH	VOLTAGE	DRIVER	CIRCUITS	MOUNTING/SUSPENSION	BATTERY (OPTIONAL)	OTHER (OPTIONAL)
4 4' 8 8' 12 12' 16 16' 20 20' 24 24'	W white AP aluminum paint	120 120 V 277 277 V 347 347 V ⁽¹⁾ UNV universal	DP dimming (0-10V) 1% D dimming (0-10V) 5% 347V standard ⁽²⁾ LT Lutron ⁽³⁾	1 1 circuit	CA(#) drywall+cable length (36" std.) CT9(#) TB/TG 9/16+cable length (36" std.) CT15(#) TB/TG 15/16+cable length (36" std.)	B# battery pack (integral)	F fuse
		(1) D dimming (0-10V) 5%	(2) For 347V only (3) Hi-Lume A Series L3D		See Ceiling Mount Guide for more details	For minimum 4' long fixture only	Requires 120V or 277V



Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+. Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.