

AURA 2x2

RECESSED

QuickShip+



The perfect blend of lighting performance and timeless aesthetic. Aura features a triple lens design with a ribbed center optical diffuser that provides balanced brightness and visual comfort. High-performance LED technology combined with the flexibility of optional integral controls deliver considerable energy savings. Aura is ideal for a variety of indoor applications including offices, institutions and commercial spaces. Installation and maintenance are made easy with toolless lens installation and access to all components from below.



Maximum Order Size - 200 units

14 calendar days or less

Ordering Guide

PRODUCT ID		SIZE	NOMINAL LUMENS		CRI		COLOUR TEMP.		SHIELDING		FINISH	
AULED	Aura	22 2'X2'	2500	2500 lm	80	80 CRI	30	3000 K	SO	spotless optics	W	white
			3000	3000 lm			35	3500 K				
			4000	4000 lm								
			4400	4400 lm								

VOLTAGE		DRIVER	CIRCUITS	MOUNTING		BATTERY (OPTIONAL)		OTHER (OPTIONAL)		
120	120 V	DP dimming (0-10V) 1%	1	1 circuit	TB9	t-bar 9/16"	B#	battery pack	F fuse ⁽⁴⁾	
277	277 V	D dimming (0-10V) 5% 347V standard ⁽²⁾			TB15	t-bar 15/16"			FW(#) flex whip (6' std)	
347	347 V ⁽¹⁾	LT Lutron ⁽³⁾			ST	screw slot t-bar			CP Chicago plenum	
UNV	universal				TG9	tegular 9/16"				
					TG15	tegular 15/16"				
					DF	drywall flange				
(1) D dimming (0-10V) 5% standard		(2) For 347V only (3) Hi-Lume A Series L3D						Please consult factory		(4) Requires 120V or 277V



Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.

Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.

August 2019