



**Beam 6 LED** is a compact, linear system with multiple lighting, mounting, and design options, suitable for large spaces and high ceilings. It delivers efficient direct light distributions, with optional MR16 accents. IC Controls equip a BEAM 6 LED system to reduce energy consumption further still.



\*Check the latest update on the DLC website for complete information. Not all versions may be DLC qualified.



Maximum Order Size - 200 Feet

**14 calendar days or less**

**Ordering Guide**

PRODUCT ID		NOM. LUMENS/FT		CRI		COLOR TEMP.		SHIELDING		LENGTH		
<b>B6SLED</b>	BEAM 6 Surface LED	<b>400</b>	400 lm/ft	<b>80</b>	80 CRI	<b>30</b>	3000 K	<b>SO</b>	spotless lens	<b>2</b>	2'	
		<b>500</b>	500 lm/ft				<b>4</b>			4'		
		<b>750</b>	750 lm/ft				<b>6</b>			6'		
		<b>1000</b>	1000 lm/ft				<b>8</b>			8'		
							<b>10</b>			10'		
										<b>12</b>	12'	
										<b>S#</b>	system run <sup>(1)</sup>	
										Use spotless lens		(1) In 4" increments only

FINISH		VOLTAGE		DRIVER		CIRCUITS		MOUNTING		BATTERY (OPTIONAL)		OTHER (OPTIONAL)					
<b>W</b>	white	<b>120</b>	120 V	<b>DP</b>	dimming (0-10V) 1%	<b>1</b>	1 circuit	<b>S</b>	surface drywall ceiling	<b>B#</b>	battery pack 4' sections	<b>F</b>	fuse				
		<b>277</b>	277 V											<b>D</b>	dimming (0-10V) 5% 347V standard <sup>(3)</sup>	<b>FW#</b>	flex whip (6' std)
		<b>347</b>	347 V <sup>(2)</sup>														
		<b>UNV</b>	universal														
		(2) D dimming (0-10V) 5% standard	(3) For 347V only					Please consult factory		Requires 120V or 277V							
			(4) Hi-Lume A Series L3D														



**i** Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+. Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.  
August 2019