



Ordering Guide (fill out green boxes to complete code)

SCSS				UB		
PRODUCT ID	NOM.LUMENS/FT	CRI	COLOR TEMP.	SHIELDING	TOTAL LENGTH	FINISH
SCSS SideStep Hexagon Pendant	300 300 lm/ft - Minimum	80 80 CRI	27 2700 K	UB Ultra blend lens	H2 2 feet segments	W white
	500 500 lm/ft - Maximum	90 90 CRI*	30 3000 K			BLK black
			35 3500 K			RAL(#) pick your RAL*
			40 4000 K			C(#) custom
Outputs between listed min and max are available. Consult factory for outputs outside of the listed range.						*Specify RAL#

VOLTAGE	DRIVER	CIRCUITS	MOUNTING/SUSPENSION
120 120 V	DP dimming (0-10V) 1%	1 1 circuit	CA(L) drywall+cable length (36" std.)*
277 277 V	BI bi-level dimming	2 2 circuits	CT9(L) TB/TG 9/16+cable length (36" std.)*
347 347 V	O(DALI) Digital Addressable Lighting Interface	+E(#) emergency section*	CT15(L) TB/TG15/16+cable length (36" std.)*
UNV universal	O(DMX) Digital Multiplex	+NL(#) night light section*	CTS(L) screw slot+cable length (36" std.)*
DC low voltage*	O(XSR) Xitanium SR for wireless sensor	+GTD(#) generator transfer device*	CASL(L) drywall cable sloped ceiling*
	POE(MOLEX) POE Molex driver		+SM seismic kit
	POE(IGOR) POE IGOR driver		
	POE(SMARTENGINE) POE Smartengine driver		
*Only available with POE drivers.		* Specify quantity	See Mounting kit guide for full specification code. *Specify length in inches.

CABLE MOUNTING TYPE	CANOPY	BATTERY (OPTIONAL)
RS Regular suspension	SC Square canopy	B(#) battery pack
SM Square monopoint	RC Round canopy	
	White canopy standard	Remote only; Not available with 347V Please consult factory

