

AURA 2x4

RECESSED

QuickShip+



The perfect blend of lighting performance and timeless aesthetic. Aura features a triple lens design with a ribbed center optical diffuser that provides balanced brightness and visual comfort. High-performance LED technology combined with the flexibility of optional integral controls deliver considerable energy savings. Aura is ideal for a variety of indoor applications including offices, institutions and commercial spaces. Installation and maintenance are made easy with toolless lens installation and access to all components from below.



Maximum Order Size - 200 units

14 calendar days or less

Ordering Guide

| PRODUCT ID | | SIZE | NOMINAL LUMENS | | CRI | | COLOUR TEMP. | | SHIELDING | | FINISH | |
|--------------|------|-----------------|----------------|---------|-----------|--------|--------------|--------|-----------|-----------------|----------|-------|
| AULED | Aura | 24 2'X4' | 3100 | 3100 lm | 80 | 80 CRI | 30 | 3000 K | SO | spotless optics | W | white |
| | | | 4500 | 4500 lm | | | 35 | 3500 K | | | | |
| | | | 5000 | 5000 lm | | | | | | | | |
| | | | 7000 | 7000 lm | | | | | | | | |
| | | | 9000 | 9000 lm | | | | | | | | |

| VOLTAGE | | DRIVER | CIRCUITS | MOUNTING | | BATTERY (OPTIONAL) | | OTHER (OPTIONAL) | |
|-----------------------------------|----------------------|--|--------------------|------------------------|------------------|--------------------|---------------------------|------------------|---------------------|
| 120 | 120 V | DP dimming (0-10V) 1% | 1 1 circuit | TB9 | t-bar 9/16" | B# | battery pack | F | fuse ⁽⁴⁾ |
| 277 | 277 V | D dimming (0-10V) 5% 347V standard ⁽²⁾ | | TB15 | t-bar 15/16" | | | FW(#) | flex whip (6' std) |
| 347 | 347 V ⁽¹⁾ | LT Lutron ⁽³⁾ | | ST | screw slot t-bar | | | CP | Chicago plenum |
| UNV | universal | | | TG9 | tegar 9/16" | | | | |
| | | | | TG15 | tegar 15/16" | | | | |
| | | | | DF | drywall flange | | | | |
| (1) D dimming (0-10V) 5% standard | | (2) For 347V only (3) Hi-Lume A Series L3D | | Please consult factory | | | (4) Requires 120V or 277V | | |



Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.

Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.

August 2019