



DIA LED troffers are high performance recessed luminaires that deliver soft ambient light via a patented VL Optic™. Light is transmitted through a luminous lens without harsh contrast. The precision center refractor and translucent side panels offer a balanced aesthetic. Best used when high efficiency and visual comfort are key.



*Check the latest update on the DLC website for complete information. Not all versions may be DLC qualified.



Maximum Order Size - 200 units

14 calendar days or less

Ordering Guide

PRODUCT ID		SIZE	NOMINAL LUMENS		CRI		COLOUR TEMP.		SHIELDING		FINISH	
DIALED	Dia LED	22 2'X2'	2500	2500 lm	80	80 CRI	30	3000 K	VL	VL optics	W	white
			3000	3000 lm			35	3500 K				
			4000	4000 lm								
			4400	4400 lm								

VOLTAGE		DRIVER		CIRCUITS		MOUNTING		BATTERY (OPTIONAL)		OTHER (OPTIONAL)	
120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	TB9	t-bar 9/16"	B#	battery pack	F	fuse ⁽⁴⁾
277	277 V	D	dimming (0-10V) 5% 347V standard ⁽²⁾			TB15	t-bar 15/16"			FW(#)	flex whip (6' std)
347	347 V ⁽¹⁾	LT	Lutron ⁽³⁾			ST	screw slot t-bar			CP	Chicago plenum
UNV	universal					TG9	tegular 9/16"				
						TG15	tegular 15/16"				
						DF	drywall flange				
(1) D dimming (0-10V) 5% standard		(2) For 347V only (3) Hi-Lume A Series L3D						Please consult factory		(4) Requires 120V or 277V	



Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+. Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information. August 2019