



**Beam 6 LED** is a compact, linear system with multiple lighting, mounting, and design options, suitable for large spaces and high ceilings. It delivers efficient direct light distributions, with optional MR16 accents. IC Controls equip a BEAM 6 LED system to reduce energy consumption further still.



\*Check the latest update on the DLC website for complete information. Not all versions may be DLC qualified.



Maximum Order Size - 200 Feet

**14 calendar days or less**

**Ordering Guide**

PRODUCT ID		NOM. LUMENS/FT		CRI		COLOR TEMP.		SHIELDING		LENGTH	
<b>B6DLED</b>	BEAM 6 Pendant LED	<b>400</b>	400 lm/ft	<b>80</b>	80 CRI	<b>30</b>	3000 K	<b>SO</b>	spotless lens	<b>2</b>	2'
		<b>500</b>	500 lm/ft				<b>4</b>			4'	
		<b>750</b>	750 lm/ft				<b>6</b>			6'	
		<b>1000</b>	1000 lm/ft				<b>8</b>			8'	
							<b>10</b>			10'	
										<b>12</b>	12'
										<b>S#</b>	system run <sup>(1)</sup>
									Use spotless lens	(1) In 4' increments only	

FINISH		VOLTAGE		DRIVER		CIRCUITS		MOUNTING		BATTERY (OPTIONAL)		OTHER (OPTIONAL)	
<b>W</b>	white	<b>120</b>	120 V	<b>DP</b>	dimming (0-10V) 1%	<b>1</b>	1 circuit	<b>CA(#)</b>	drywall+cable length (36" std.)	<b>B#</b>	battery pack 4' sections	<b>F</b>	fuse
<b>AP</b>	aluminum paint	<b>277</b>	277 V	<b>D</b>	dimming (0-10V) 5% 347V standard <sup>(3)</sup>			<b>CT9(#)</b>	TB/TG 9/16+cable length (36" std.)				
		<b>347</b>	347 V <sup>(2)</sup>	<b>LT</b>	Lutron <sup>(4)</sup>	<b>CT15(#)</b>	TB/TG 15/16+cable length (36" std.)						
		(2) D dimming (0-10V) 5% standard		(3) For 347V only (4) Hi-Lume A Series L3D				<a href="#">See Ceiling Mount Guide for more details</a>		Please consult factory		Requires 120V or 277V	



**Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.** Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information. August 2019