



When you're looking for a basic mid-size pendant that is powered by Axis Lighting's **SurroundLite** technology, **Slim** Pendant is a great choice. With its wide 360 degree uplight distribution, discover how you can eliminate luminaires or use shorter luminaires in your design without compromising light levels, light quality and visual comfort. You have to see it to believe it!



Maximum Order Size - 200 Feet

**14 calendar days or less**

**Ordering Guide**

PRODUCT ID		LIGHT ENGINE		NOMINAL LUMENS/FT		CRI		COLOR TEMPERATURE		SHIELDING		FIXTURE LENGTH		
<b>SLED</b>	Slim SurroundLite Pendant LED	<b>SL 0/100</b>	SurroundLite 0% up/100% down	<b>800</b> 800 lm/ft	1000 1000 lm/ft	<b>80</b>	80 CRI	<b>30</b> 3000 K	<b>35</b> 3500 K	<b>VL</b> VL optic	<b>SM</b> smooth lens	<b>4</b> 4'	<b>8</b> 8'	
												<b>12</b> 12'	<b>S#</b> system runs <sup>(1)</sup>	
											Consult factory for other lumen packages		(1) In 4' increments only	

FINISH		VOLTAGE		DRIVER		CIRCUITS		MOUNTING/SUSPENSION		BATTERY (OPTIONAL)		OTHER(OPTIONAL)	
<b>W</b>	white	<b>120</b>	120 V	<b>DP</b>	dimming (0-10V) 1%	<b>1</b>	1 circuit	<b>CA(#)</b>	drywall+cable length (36" std.)	<b>B#</b>	battery pack (integral)	<b>F</b>	fuse
<b>AP</b>	aluminum paint	<b>277</b>	277 V	<b>D</b>	dimming (0-10V) 5% 347V standard <sup>(3)</sup>			<b>CT9(#)</b>	TB/TG 9/16+cable length (36" std.)				
		<b>347</b>	347 V <sup>(2)</sup>	<b>LT</b>	Lutron <sup>(4)</sup>			<b>CT15(#)</b>	TB/TG 15/16+cable length (36" std.)				
		<b>UNV</b>	universal										
		(2) D dimming (0-10V) 5% standard		(3) For 347V only (4) Hi-Lume A Series L3D				<a href="#">See Ceiling Mount Guide for more details</a>		For minimum 4' long fixture only		Requires 120V or 277V	

**1** Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.



Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.

August 2019