




Right Angle mount (R)



### MOUNTING SIDE



Please provide elevation view



Project \_\_\_\_\_

Type \_\_\_\_\_


Notes \_\_\_\_\_

### PERFORMANCE PER LINEAR FOOT AT 3500K

NOMINAL LUMEN OUTPUT	INPUT WATTS*	EFFICACY
250 lm/ft	2.39 W/ft	105 lm/W
500 lm/ft	4.77 W/ft	105 lm/W
850 lm/ft	8.11 W/ft	105 lm/W
1000 lm/ft	9.55 W/ft	105 lm/W

\*Please consult factory for custom lumen output and wattage.

### LIGHT DISTRIBUTION (EXAMPLE AS-SF 500 LUMENS UP)



NOTE: Rotate distribution 90° when luminaire is mounted on ceiling.



### Ordering Guide

PSK	PRODUCT ID	MOUNTING SIDE	OPTIC-STEP SIDE	OPTIC-FLAT SIDE	NOM. LUMENS/FT
PSK	Pose Knife Edge	R right angle	AS asymmetric - step side	SF solid - flat side	250 250 lm/ft - Min 1000 1000 lm/ft - Max
			See light distribution options above	See light distribution options above	Outputs between listed min and max are available. Consult factory for outputs outside of the listed range.

CRI	COLOR TEMP.	LENGTH	FINISH	VOLTAGE	DRIVER
80 80 CRI	27 2700 K	2 2'	AP aluminum paint	120 120 V	DP dimming (0-10V) 1% - integral*
90 90 CRI	30 3000 K	3 3'	W white	277 277 V	POE(#) POE drivers**
	35 3500 K	4 4'	BLK black	347 347 V*	
	40 4000 K	5 5'	C custom	UNV universal	
		6 6'		DC low voltage**	
		7 7'			
		8 8'			
		S(L) system run*			
2 ft min, 1 ft increment, 8ft max stand alone. For all other lengths and related outputs, please consult factory.				* Remote driver only. ** Only available with POE drivers.	*Integral driver ** Specify system

CIRCUITS	MOUNTING	REMOTE BATTERY (OPTIONAL)	OTHER (OPTIONAL)	CUSTOM (OPTIONAL)
1 1 circuit 2 2 circuits* +E(#) emergency circuit **	MT mounting track for drywall and solid ceiling	B(#) remote battery pack	EF end feed*	C custom
*To control sections separately ** Specify quantity	For drywall and solid ceiling mounting. Please consult factory for power feed options available for your ceiling type and application.		*Not available with flex whip wiring.	Please specify

### ● SPECIFICATIONS

#### CONSTRUCTION

<b>Housing</b>	Extruded aluminum (0.07" nominal) Up to 70% recycled content
<b>End Cap</b>	Cast aluminum
<b>Interior Brackets</b>	Die formed sheet steel (22 gauge)
<b>Reflectors</b>	White powder coated sheet steel (24 gauge)
<b>Lenses</b>	Extruded acrylic (0.070" nominal)

### ● ELECTRICAL

<b>Power over Ethernet</b>	MOLEX
<b>POE drivers*</b>	IGOR
(consult factory for more information)	SMARTENGINE
UL2108 certified for integral or remote driver	O - Other (Consult factory)

**Emergency** Remote emergency battery pack or emergency circuit optional.

**Input Voltage** 120V, 277V, 347V (remote), UNV.

**i** Incorporating these components may have limitations or affect the length of the luminaire, please contact factory for more details.

### ● LED SYSTEM

<b>CRI</b>	Minimum 80 or 90 color rendering index.
<b>CCT</b>	Choice of 2700K, 3000K, 3500K and 4000K color temperature with a great color consistency (within 3-step MacAdam ellipse). Both within fixture and fixture to fixture. Consult factory for other color temperatures
<b>LED life</b>	Minimum 50,000h with 85% of lumen maintenance in 25°C ambient temperature, in compliance with IES LM-80 testing measurements.
<b>Thermal Management</b>	Aluminum housing acting as the heat sink to maximize life.
<b>Environment</b>	Dry and damp rated for indoor use only in operating ambient temperatures of 0-40°C (32-104°F).

### ● OPTICS



CL Clear Lens

### ● SYSTEM (S(L))

POSE™ linear systems, with the use of a strong profile, allow for a connection system of continuous runs.

Lengths of 2' min, 1' increments, 8' max stand alone as well as custom lengths are available.

Runs of POSE™ that are greater than 8' in length are designated as systems (S(L)). This means that the run is comprised of a combination of sections to be assembled on site using our joining system. For more information on systems and joining, please refer to the POSE™ installation sheets available for download at [www.axislighting.com](http://www.axislighting.com).

### ● WARRANTY


Limited 5-year warranty is available. Warranty is valid provided luminaires are installed and used according to specifications. For full terms and conditions, please consult warranty section at [axislighting.com](http://axislighting.com).

## Mounting flexibility, multiple application solutions


Use mounting track (MT) for wall or ceiling mount.

### MOUNTING TRACK (MT)

flush with wall or surface



### ● PHOTOMETRIC DATA




asymmetric on step side  
 solid on flat side

LUMENS %  
 100%  
 0%

Uplight 100%  
 300 lm/ft

#### PHOTOMETRIC CURVE



**Lumen/ft up: 330 lm/ft**  
**Total Lumens: 660 lm (for 2ft)**  
**Input Watts: 6.29 W**  
**Efficacy: 105 lm/W**

#### CANDELA DISTRIBUTION

Vertical Angle	Horizontal Angles				
	0	22.5	45	67.5	90
85	0	0	0	0	0
90	0	1	1	1	1
95	11	1	1	1	1
105	47	14	4	3	3
115	81	35	18	12	10
125	103	54	32	23	21
135	112	68	43	32	29
145	112	77	53	41	37
155	109	83	63	52	48
165	105	91	76	68	64
175	102	97	94	91	89
180	101	101	101	101	101

#### ZONAL LUMENS

Zone	Lumens
80-90	36
90	109
90-100	129
100-110	122
110-120	99
120-130	75
130-140	51
140-150	29
150-160	10
160-170	54
170-180	109
180	

80 CRI shown. For 90 CRI, divide wattage by 0.8 and multiply efficacy by 0.8.

IES FILE: PSK-2-R-AS-300-80-3500-W-120-DP-1.IES

TESTED ACCORDING TO IES LM-79-2008

**i** All IES files are available for download at: [www.axislighting.com](http://www.axislighting.com)