





Project _____


Type _____

Notes _____




6ft Curved Square:

- 1 x Framework: 4ft segments (4) + LC90 Hub (4)
- 2 x AxisTrak™ Inserts (4ft)



7ft Curved Square:

- 1 x Framework: 5ft segments (4) + LC90 Hub (4)
- 2 x AxisTrak™ Inserts (5ft)
- 2 x Indirect Surrounlite Inserts (5ft)



8ft Curved Square:

- 1 x Framework: 6ft segments (4) + LC90 Hub (4)
- 2 x AxisTrak™ Inserts (6ft)
- 2 x Indirect Surrounlite Inserts (6ft)



6x10ft Curved Rectangle:

- 1 x Framework: 4ft segments (6) + LC90Hub (4) + I180 (2)
- 2 x AxisTrak™ Inserts (4ft)



7x12ft Curved Rectangle:

- 1 x Framework: 5ft segments (6) + LC90Hub (4) + I180 (2)
- 2 x AxisTrak™ Inserts (5ft)
- 2 x Indirect Surrounlite Inserts (5ft)



8x14ft Curved Rectangle:

- 1 x Framework: 6ft segments (6) + LC90Hub (4) + I180(2)
- 2 x AxisTrak™ Inserts (6ft)
- 2 x Indirect Surrounlite Inserts (6ft)

Patented Design

Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.



Project _____

Type _____

Notes _____

AxisTrak™ decoratives must be ordered separately. Please follow the link:



Ordering Guide Framework

PRODUCT ID	FINISH	UNV VOLTAGE	CONTROLS	CIRCUITS	MOUNTING/SUSPENSION	CANOPY
6 foot Curved Square Pendant 7 foot Curved Square Pendant 8 foot Curved Square Pendant 6x10 foot Curved Rectangle Pendant 7x12 foot Curved Rectangle Pendant 8x14 foot Curved Rectangle Pendant	BLK black W white AP aluminum paint C(#) custom*	UNV universal	IMW Integral Modular Wiring for 0-10V dimming (1%) with DP integral driver IMWD Integral Modular Wiring for DALI 2.0 with DALIDT6 integral driver	Number of circuits will depend on the ordered kit, and matches lighting Zone count	CA(#) drywall+cable length (36" std.) SLV(#) drywall+stem length <48" (18" std.) leveling	RC round canopy SC square canopy*
					Specify suspension length * See Mounting kit guide for full specification code . White canopy standard. Other canopies are available. Please visit the link above.	*Not available with (SLV) stem mounting.

Ordering Guide Linear Lighting Inserts

SFLDAXT PRODUCT ID	TOTAL LENGTH	UNV VOLTAGE	CONTROLS	HOUSING FINISH
SFLDAXT StencilFlex® AxisTrak™ Insert	4 4' 5 5' 6 6'	UNV universal	DPCV integral 48V driver 60W max. 0-10V dimming through two added contacts on AxisTrak™ DALIDT6CV integral 48V driver 60W max. DALI dimming through two added contacts on AxisTrak™	BLK black W white
		Wired for 120V to determine power drops.		! Please be mindful of your Framework Color Selection when selecting your insert housing finish.

PRODUCT ID	TOTAL LENGTH	TOTAL LUMENS/FT	CRI	COLOR TEMP.	VOLTAGE	CONTROLS
SFLISL StencilFlex® Indirect SurroundLite Insert	5 5'* 6 6'	175 175 lm/ft 250 250 lm/ft 350 350 lm/ft 500 500 lm/ft 700 700 lm/ft 1000 1000 lm/ft	80 80 CRI 90 90 CRI	27 2700 K 30 3000 K 35 3500 K 40 4000 K	UNV universal	DP integral driver 0-10V dimming (1%) - wired DALIDT6 integral driver DALI 2.0 Type 6 - wired
*2 feet lit segment.						

Patented Design

Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.