



Ordering Guide (fill out green boxes to complete code)

SCDPAT		OPR(60,3)			
PRODUCT ID	PATTERNS	CORNER ID (degrees, qty)	NOM. LUMENS/FT	CRI	COLOR TEMP.
SCDPAT Sculpt Triangle Pendant Direct	T2 2 feet segments T3 3 feet segments T4 4 feet segments	OPR(60,3) regular lit corner degrees quantity 3	300 300 lm/ft - Min. 900 900 lm/ft - 90 CRI Max. 1000 1000 lm/ft - 80 CRI Max.	80 80 CRI 90 90 CRI	27 2700 K 30 3000 K 35 3500 K 40 4000 K
			Outputs between listed min and max are available. Consult factory for outputs outside of the listed range.		

SHIELDING		NL	FINISH	VOLTAGE	DRIVER
FL flush	RG 0.5" regressed	SPECIFY LENGTH			
		NL nominal	W white BLK black RAL(#) pick your RAL* C(#) custom	120 120 V 277 277 V 347 347 V UNV universal DC low voltage*	DP dimming (0-10V) 1% BI bi-level dimming O(DALI) Digital Addressable Lighting Interface O(DMX) Digital Multiplex O(XSR) Xitanium SR for wireless sensor POE(MOLEX) POE Molex driver POE(IGOR) POE IGOR driver POE(SMARTENGINE) POE Smartengine driver
All lens options use spotless lens			* Specify RAL#	* Only available with POE drivers.	* Specify system

CIRCUITS	MOUNTING	BATTERY - REMOTE (OPTIONAL)
1 1 circuit 2 2 circuits +E(#) emergency section * +NL(#) night light section * +GTD(#) generator transfer device *	CA(#) drywall+cable length (36" std.)* CT9(#) TB/TG 9/16+cable length (36" std.)* CT15(#) TB/TG15/16+cable length (36" std.)* CTS(#) screw slot+cable length (36" std.)* CASL(#) drywall cable sloped ceiling* +SM seismic kit	B(#) remote battery pack
* Specify quantity	See Mounting kit guide for full specification code. *Specify length in inches.	Remote only, Please consult factory

