



This compact, efficient extruded aluminum linear pendant with trim helps create visually comfortable spaces with a subtle glow. Versatile and classic, will fit many applications to provide a good ambient light layer as well as vertical illumination from a primarily direct source.



\*Check the latest update on the DLC website for complete information. Not all versions may be DLC qualified.



Maximum Order Size - 200 Feet

14 calendar days or less

### Ordering Guide

PRODUCT ID	NOMINAL LUMENS/FT	CRI	COLOR TEMPERATURE	SHIELDING	LENGTH/FT
<b>MBLED</b> Mini Box Pendant LED	<b>500</b> 500 lm/ft	<b>80</b> 80 CRI	<b>30</b> 3000 K	<b>S</b> satin lens	<b>2</b> 2'
	<b>600</b> 600 lm/ft		<b>35</b> 3500 K		<b>4</b> 4'
	<b>800</b> 800 lm/ft				<b>8</b> 8'
	<b>1000</b> 1000 lm/ft				<b>12</b> 12'
Consult factory for other lumen packages					<b>S#</b> system runs <sup>(1)</sup>
					(1) In 4' increments only

FINISH	VOLTAGE	DRIVER	CIRCUITS	MOUNTING/SUSPENSION	BATTERY (OPTIONAL)	OTHER (OPTIONAL)
<b>W</b> white	<b>120</b> 120 V	<b>DP</b> dimming (0-10V) 1%	<b>1</b> 1 circuit	<b>CA(#)</b> drywall+cable length (36" std.)	<b>B#</b> battery pack 4' sections	<b>F</b> fuse
<b>AP</b> aluminum paint	<b>277</b> 277 V	<b>D</b> dimming (0-10V) 5% 347V standard <sup>(3)</sup>		<b>CT9(#)</b> TB/TG 9/16+cable length (36" std.)		
	<b>347</b> 347 V <sup>(1)</sup>	<b>LT</b> Lutron <sup>(4)</sup>		<b>CT15(#)</b> TB/TG 15/16+cable length (36" std.)		
	<b>UNV</b> universal					
	(2) D dimming (0-10V) 5%	(3) For 347V only (4) Hi-Lume A Series L3D		<a href="#">See Ceiling Mount Guide for more details</a>	Specify quantity Please consult factory	Requires 120V or 277V

**1** Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+. Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information. August 2019