




Beam 6 LED: for a clean, uniform, continuous end-to-end luminous effect from a best-selling recessed linear luminaire that naturally compliments any architectural design with minimal intrusion. Great for shallow ceiling spaces and available with multiple lengths and lumen packages to provide the right amount of light for the allowed wattage.



Flush lens shown



*Check the latest update on the DLC website for complete information. Not all versions may be DLC qualified.



Maximum Order Size - 200 Feet

14 calendar days or less

Ordering Guide

PRODUCT ID		NOM. LUMENS/FT		CRI		COLOR TEMP.		SHIELDING		LENGTH						
B6RLED	BEAM 6 Recessed LED	400	400 lm/ft	80	80 CRI	30	3000 K	FL	flush	4	4'					
		500	500 lm/ft				35		3500 K		RG	regressed	6	6'		
		750	750 lm/ft									8		8'		
		1000	1000 lm/ft												12	12'
		S#	system run ⁽¹⁾													
									Use spotless lens	(1) In 4' increments only						

FINISH		VOLTAGE		DRIVER		CIRCUITS		MOUNTING		BATTERY (OPTIONAL)		OTHER (OPTIONAL)	
W	white	120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	TB9	t-bar 9/16"	B#	battery pack 4' sections	EF	end feed
		277	277 V	D	dimming (0-10V) 5% 347V standard ⁽³⁾			TB15	t-bar 15/16"			FW(#)	flex whip (6' std)
		347	347 V ⁽²⁾	LT	Lutron ⁽⁴⁾			ST	screw slot t-bar			CP	Chicago plenum
		UNV	universal					TG9	tegar 9/16"			HD	hold down clip
								TG15	tegar 15/16"			F	fuse ⁽⁵⁾
								DF	drywall flange	Please consult factory		(5) Requires 120V or 277V	
								DS	drywall spackle flange				

(2) D dimming (0-10V) 5% standard

(3) For 347V only
(4) Hi-Lume A Series L3D

Please consult factory

(5) Requires 120V or 277V



Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+. Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.
August 2019