



**Beam 4 LED:** for a clean, uniform, continuous end-to-end luminous effect from a best-selling recessed linear luminaire that naturally compliments any architectural design with minimal intrusion. Great for shallow ceiling spaces and available with multiple lengths and lumen packages to provide the right amount of light for the allowed wattage.



\*Check the latest update on the DLC website for complete information. Not all versions may be DLC qualified.



Maximum Order Size - 400 Feet

**14 calendar days or less**

**Ordering Guide**

PRODUCT ID	NOM. LUMENS/FT	CRI	COLOR TEMP.	SHIELDING	LENGTH
<b>BBSLED</b> BEAM 4 Surface LED	<b>400</b> 400 lm/ft	<b>80</b> 80 CRI	<b>30</b> 3000 K	<b>SO</b> spotless lens	<b>2</b> 2'
	<b>500</b> 500 lm/ft		<b>35</b> 3500 K		<b>4</b> 4'
	<b>750</b> 750 lm/ft				<b>6</b> 6'
	<b>1000</b> 1000 lm/ft				<b>8</b> 8'
					<b>10</b> 10'
					<b>12</b> 12'
					<b>S#</b> system run <sup>(1)</sup>
				Use spotless lens	(1) In 4' increments only

FINISH	VOLTAGE	DRIVER	CIRCUITS	MOUNTING	BATTERY (OPTIONAL)	OTHER (OPTIONAL)
<b>W</b> white	<b>120</b> 120 V <b>277</b> 277 V <b>347</b> 347 V <sup>(2)</sup> <b>UNV</b> universal	<b>DP</b> dimming (0-10V) 1% <b>D</b> dimming (0-10V) 5% 347V standard <sup>(3)</sup> <b>LT</b> Lutron <sup>(4)</sup>	<b>1</b> 1 circuit	<b>S</b> surface drywall ceiling	<b>B#</b> battery pack 4' sections	<b>F</b> fuse <b>FW#</b> flex whip (6' std)
	(2) D dimming (0-10V) 5% standard	(3) For 347V only (4) Hi-Lume A Series L3D			Not available in 2' Please consult factory	Requires 120V or 277V



**Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.** Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.  
August 2019