



Ideal for an ambient light applications that require a mostly uplight component in a small profile pendant that's full of power. Also powered by Axis Lighting's **SurroundLite** technology, **Twig** delivers a wide 360 degree uplight distribution that can eliminate luminaires or result in use of shorter luminaires without compromising light level, light quality and visual comfort. You have to see it to believe it!



Maximum Order Size - 200 Feet

14 calendar days or less

### Ordering Guide

PRODUCT ID		LIGHT ENGINE		NOMINAL LUMENS/FT		CRI		COLOR TEMPERATURE		SHIELDING	
<b>TWRLED</b>	Twig SurroundLite Pendant LED	<b>SL 90/10</b>	SurroundLite 90% up/10% down	<b>750</b>	750 lm/ft	<b>80</b>	80 CRI	<b>30</b>	3000 K	<b>VL</b>	VL optic
				<b>1000</b>	1000 lm/ft			<b>35</b>	3500 K	<b>SO</b>	spotless lens
				<b>1250</b>	1250 lm/ft						
				Consult factory for other lumen packages							

FIXTURE LENGTH		FINISH		VOLTAGE		DRIVER		CIRCUITS		MOUNTING/SUSPENSION		BATTERY (OPTIONAL)		OTHER (OPTIONAL)	
<b>4</b>	4'	<b>W</b>	white	<b>120</b>	120 V	<b>DP</b>	dimming (0-10V) 1%	<b>1</b>	1 circuit	<b>CA(#)</b>	drywall+cable length (36" std.)	<b>B#</b>	battery pack (integral)	<b>F</b>	fuse
<b>8</b>	8'	<b>AP</b>	aluminum paint	<b>277</b>	277 V	<b>D</b>	dimming (0-10V) 5% 347V standard <sup>(3)</sup>			<b>CT9(#)</b>	TB/TG 9/16+cable length (36" std.)				
<b>12</b>	12'			<b>347</b>	347 V <sup>(2)</sup>	<b>LT</b>	Lutron <sup>(4)</sup>			<b>CT15(#)</b>	TB/TG 15/16+cable length (36" std.)				
<b>S#</b>	system runs <sup>(1)</sup>			<b>UNV</b>	universal										
(1) In 4' increments only				(2) D dimming (0-10V) 5%		(3) For 347V only (4) Hi-Lume A Series L3D				<a href="#">See Ceiling Mount Guide for more details</a>		For minimum 48" long fixture only		Requires 120V or 277V	

