



When you're looking for a basic mid-size pendant that is powered by Axis Lighting's **SurroundLite** technology, **Slim** Pendant is a great choice. With its wide 360 degree uplight distribution, discover how you can eliminate luminaires or use shorter luminaires in your design without compromising light levels, light quality and visual comfort. You have to see it to believe it!



Maximum Order Size - 200 Feet

14 calendar days or less

Ordering Guide

PRODUCT ID		LIGHT ENGINE		NOMINAL LUMENS/FT		CRI		COLOR TEMPERATURE		SHIELDING		FIXTURE LENGTH	
SLED	Slim SurroundLite Pendant LED	SL 80/20	SurroundLite 80% up/20% down	800	800 lm/ft	80	80 CRI	30	3000 K	VL	VL optic	4	4'
				1000	1000 lm/ft			35	3500 K			SM	smooth lens
				Applies to both UP & DOWN. Consult factory for other lumen packages		Applies to both UP & DOWN.		Applies to both UP & DOWN.				(1) In 4' increments only	

FINISH		VOLTAGE		DRIVER		CIRCUITS		MOUNTING/SUSPENSION		BATTERY (OPTIONAL)		OTHER (OPTIONAL)	
W	white	120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	CA(#)	drywall+cable length (36" std.)	B#	battery pack (integral)	F	fuse
AP	aluminum paint	277	277 V	D	dimming (0-10V) 5% 347V standard ⁽²⁾			CT9(#)	TB/TG 9/16+cable length (36" std.)				
		347	347 V ⁽¹⁾	LT	Lutron ⁽³⁾			CT15(#)	TB/TG 15/16+cable length (36" std.)				
		UNV	universal					See Ceiling Mount Guide for more details		For minimum 4' long fixture only		Requires 120V or 277V	
		(1) D dimming (0-10V) 5%		(2) For 347V only (3) Hi-Lume A Series L3D									

i Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.



Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.

August 2019