



Beam 4 LED: for a clean, uniform, continuous end-to-end luminous effect from a best-selling recessed linear luminaire that naturally compliments any architectural design with minimal intrusion. Great for shallow ceiling spaces and available with multiple lengths and lumen packages to provide the right amount of light for the allowed wattage.







*Check the latest update on the DLC website for complete information Not all versions may be DLC qualified.





Maximum Order Size - 400 Feet

14 calendar days or less

Ordering Guide

PR	RODUCT ID	NOM. LUMENS/FT	CRI		COLOR TEMP.		SHIELDING		LENGTH
BBRLED BEA	AM 4 Recessed LED	400 400 lm/ft 500 500 lm/ft 750 750 lm/ft 1000 1000 lm/ft	80 80 CRI		3000 K 3500 K		flush regressed		6'
,						All lens options use spotless lens		(1) In 4' increments only	

FINISH	VOLTAGE	DRIVER	CIRCUITS	MOUNTING	BATTERY (OPTIONAL)	OTHER (OPTIONAL)
W white	120 V 277 277 V 347 347 V ⁽²⁾ UNV universal	DP dimming (0-10V) 1% D dimming (0-10V) 5% 347V standard (3) LT Lutron (4)	1 1 circuit	TB9 t-bar 9/16" TB15 t-bar 15/16" ST screw slot t-bar TG9 tegular 9/16" TG15 tegular 15/16" DF drywall flange DS drywall spackle flange	B# battery pack 4' sections	FW(#) end feed flex whip (6' std) CP Chicago plenum hold down clip F fuse (4)
	(2) D dimming (0-10V) 5% standard	(3) For 347V only (4) Hi-Lume A Series L3D			Please consult factory	(4) Requires 120V or 277V

