



**DIA LED** troffers are high performance recessed luminaires that deliver soft ambient light via a patented VL Optic™. Light is transmitted through a luminous lens without harsh contrast. The precision center refractor and translucent side panels offer a balanced aesthetic. Best used when high efficiency and visual comfort are key.



Maximum Order Size - 200 units

14 calendar days or less

### Ordering Guide

PRODUCT ID		SIZE	NOMINAL LUMENS		CRI		COLOUR TEMP.		SHIELDING		FINISH	
<b>DIALED</b>	Dia LED	<b>24</b> 2'X4'	<b>3100</b>	3100 lm	<b>80</b>	80 CRI	<b>30</b>	3000 K	<b>VL</b>	VL optics	<b>W</b>	white
			<b>4500</b>	4500 lm			<b>35</b>	3500 K				
			<b>5000</b>	5000 lm								
			<b>7000</b>	7000 lm								
			<b>9000</b>	9000 lm								

VOLTAGE		DRIVER		CIRCUITS		MOUNTING		BATTERY (OPTIONAL)		OTHER (OPTIONAL)	
<b>120</b>	120 V	<b>DP</b>	dimming (0-10V) 1%	<b>1</b>	1 circuit	<b>TB9</b>	t-bar 9/16"	<b>B#</b>	battery pack	<b>F</b>	fuse <sup>(4)</sup>
<b>277</b>	277 V	<b>D</b>	dimming (0-10V) 5% 347V standard <sup>(2)</sup>			<b>TB15</b>	t-bar 15/16"			<b>FW(#)</b>	flex whip (6' std)
<b>347</b>	347 V <sup>(1)</sup>	<b>LT</b>	Lutron <sup>(3)</sup>			<b>ST</b>	screw slot t-bar			<b>CP</b>	Chicago plenum
<b>UNV</b>	universal					<b>TG9</b>	tegular 9/16"				
						<b>TG15</b>	tegular 15/16"				
						<b>DF</b>	drywall flange				
(1) D dimming (0-10V) 5% standard		(2) For 347V only						Please consult factory		(4) Requires 120V or 277V	
		(3) Hi-Lume A Series L3D									

**i** Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.



Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.