

The perfect blend of lighting performance and timeless aesthetic. Aura features a triple lens design with a ribbed center optical diffuser that provides balanced brightness and visual comfort. High-performance LED technology combined with the flexibility of optional integral controls deliver considerable energy savings. Aura is ideal for a variety of indoor applications including offices, institutions and commercial spaces. Installation and maintenance are made easy with toolless lens installation and access to all components from below.





Maximum Order Size - 200 units

14 calendar days or less

Ordering Guide

PRODUCT ID	SIZE	NOMINAL LUMENS	CRI	COLOUR TEMP.	SHIELDING	FINISH
AULED Aura	14 1′X4′	3100 3100 lm 4500 4500 lm 5000 5000 lm 7000 7000 lm 9000 9000 lm	80 80 CRI	30 3000 K 35 3500 K	spotless optics	W white

VOLTAGE		DRIVER	CIRCUITS	MOUNTING		BATTERY (OPTIONAL)		OTHER (OPTIONAL)	
120	120 V	DP dimming (0-10V) 1%	1 1 circuit	TB9	t-bar 9/16"	B#	battery pack	F	fuse (4)
277	277 V	D dimming (0-10V) 5% 347V standard (2)		TB15	t-bar 15/16"			FW(#)	flex whip (6' std)
347	347 V ⁽¹⁾	LT Lutron (3)		ST	screw slot t-bar			CP	Chicago plenum
UNV	universal			TG9	tegular 9/16"				
				TG15	tegular 15/16"				
				DF	drywall flange				
(1) D dimmir	ng (0-10V) 5% standard	(2) For 347V only (3) Hi-Lume A Series L3D				Please o	consult factory	(4) Requires	s 120V or 277V

