


Combining crisp lines and a clean, rounded design. **LT SurroundLite** brings high efficiency, glare control and flexible options ideal for illuminating medium and large spaces. Exclusive SurroundLite optics produce balanced brightness, sending wide planes of light in all directions.





Maximum Order Size - 200 Feet

14 calendar days or less

Ordering Guide

	PRODUCT ID	LIGHT ENGINE		NOMINAL LUMENS/FT		CRI	COLOR TEMPERATURE		SHIELDING			
LTLED	LT SurroundLite Pendant LED	SL 80/20	SurroundLite 80% up/20% down		800 lm/ft 1000 lm/ft	80 80 CRI		3000 K 3500 K	SR	spotless lens satin ribbed lens louver		
				Consult factory	for other lumen packages							

FIXTURE LENGTH		FINISH		VOLTAGE		DRIVER		CIRCUITS		MOUNTING/SUSPENSION		BATTERY (OPTIONAL)		OTHER(OPTIONAL)	
4	4'	W	white	120	120 V	DP di	imming (0-10V) 1%	1	1 circuit	CA(#)	drywall+cable length (36" std.)	B#	battery pack (integral)	F	fuse
8	8'	AP	aluminum paint	277	277 V	D di	imming (0-10V) 5% 347V standard ⁽³⁾			CT9(#)	TB/TG 9/16+cable length (36" std.)				
12	12'			347	347 V (2)	LT Lu	utron (4)			CT15(#)	TB/TG 15/16+cable length (36" std.)				
16	16′			UNV	universal										
20	20'														
24	24'														
		(2) D dimming (0-10V) 5%		(3) For 347V only (4) Hi-Lume A Series L3D				See Ceiling Mount Guide for more details		For minimum 4' long fixture only		Requires 120V or 277V			

