



Beam 4 LED: for a clean, uniform, continuous end-to-end luminous effect from a best-selling pendant linear luminaire that naturally compliments any architectural design with minimal intrusion. Great for shallow ceiling spaces and available with multiple lengths and lumen packages to provide the right amount of light for the allowed wattage.





Maximum Order Size - 400 Feet

14 calendar days or less

Ordering Guide

PRODUCT ID		NOM. LUMENS/FT	CRI	COLOR TEMP.		SHIELDING		LENGTH	
BBDLED	BEAM 4 Pendant LED	400 400 lm/ft	80 80 CRI	30	3000 K	so	spotless lens	2	2'
		500 500 lm/ft		35	3500 K			4	4'
		750 750 lm/ft						6	6'
		1000 1000 lm/ft						8	8'
								10	10'
								12	12'
								S#	system run (1)
		Constul factory for other lumen packages				Use spotless lens		(1) In 4' increments only	

FINISH		VOLTAGE		DRIVER	CIRCUITS	MOUNTING		BATTERY (OPTIONAL)		OTHER (OPTIONAL)	
	white aluminum paint	277 347	120 V 277 V 347 V ⁽²⁾ universal	DP dimming (0-10V) 1% D dimming (0-10V) 5% 347V standard (3) LT Lutron (4)	1 1 circuit	CT9(#)	drywall+cable length (36" std.) TB/TG 9/16+cable length (36" std.) TB/TG 15/16+cable length (36" std.)	В#	battery pack 4' sections	F	fuse
		(2) D dimming (0-10V) 5% standard		(3) For 347V only (4) Hi-Lume A Series L3D		See Celling Mount Guide for more details		Please consult factory		Requires 120V or 277V	