



This compact, efficient extruded aluminum linear pendant with trim helps create visually comfortable spaces with a subtle glow. Versatile and classic, will fit many applications to provide a good ambient light layer as well as vertical illumination from a primarily direct source.



*Check the latest update on the DLC website for complete information. Not all versions may be DLC qualified.



Maximum Order Size - 200 Feet

14 calendar days or less

Ordering Guide

PRODUCT ID		NOMINAL LUMENS/FT		CRI		COLOR TEMPERATURE		SHIELDING		LENGTH/FT	
MBSLED	Mini Box Surface LED	500	500 lm/ft	80	80 CRI	30	3000 K	S	satin lens	2	2'
		600	600 lm/ft							4	4'
		800	800 lm/ft							8	8'
		1000	1000 lm/ft							12	12'
										S#	system runs ⁽¹⁾
(1) In 4' increments only											

FINISH		VOLTAGE		DRIVER		CIRCUITS		MOUNTING/SUSPENSION		BATTERY (OPTIONAL)		OTHER (OPTIONAL)							
W	white	120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	S	surface drywall ceiling	B#	battery pack 4' sections	F	fuse						
		277	277 V											D	dimming (0-10V) 5% 347V standard ⁽³⁾	FW#	flex whip (6' std)		
		347	347 V ⁽²⁾															LT	Lutron ⁽⁴⁾
		UNV	universal																
		(2) D dimming (0-10V) 5% standard	(3) For 347V only					Not available in 2' Specify quantity Please consult factory		Requires 120V or 277V									
				(4) Hi-Lume A Series L3D															

 **1** Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+. Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information. August 2019