




Please provide elevation view

RS - Right Angle Surface




Project _____

Type _____

Notes _____

- Designed for Nurses Stations and healthcare shift workers
- White LED lighting for general ambient and/or task illumination
- BeWell Optics provides visual comfort at a local level without affecting computer monitor resolution

PERFORMANCE PER LINEAR FOOT AT 3500K
WITH ALL OPTICS OPTIONS

NOMINAL LUMEN OUTPUT	INPUT WATTS*	EFFICACY
250 lm/ft	2.37 W/ft	105 lm/W
500 lm/ft	4.74 W/ft	105 lm/W
850 lm/ft	8.06 W/ft	105 lm/W
1000 lm/ft	9.49 W/ft	105 lm/W

Please consult factory for custom lumen output and wattage.

LIGHT DISTRIBUTION

STEP SIDE FLAT SIDE	AS	AF	asymmetric on step side	50%	LS	LF	lambertian on step side	50%
			asymmetric on flat side	50%			lambertian on flat side	50%
	AS	LF	asymmetric on step side	60%	LS	AF	lambertian on step side	40%
			lambertian on flat side	40%			asymmetric on flat side	60%

*See page 6 for photometry



Ordering Guide


PS	BC	R			
PRODUCT ID	LINE	MOUNTING SIDE	OPTIC-STEP SIDE	OPTIC-FLAT SIDE	NOM. LUMENS/FT
PS Pose	BC BalancedCare™	R right angle	AS asymmetric - step side LS lambertian - step side	AF asymmetric - flat side LF lambertian - flat side	250 250 lm/ft 500 500 lm/ft 850 850 lm/ft 1000 1000 lm/ft
			See light distribution options above AS & LS comes with UB ultra blend lens	See light distribution options above AF & LF comes with UB ultra blend lens	Outputs between listed min and max are available. Consult factory for outputs outside of the listed range.

CRI	COLOR TEMP.	LENGTH	FINISH	VOLTAGE	DRIVER
80 80 CRI 90 90 CRI	27 2700 K 30 3000 K 35 3500 K 40 4000 K	2 2' 3 3' 4 4' S(L) system run*	AP aluminum paint W white BLK black C custom	120 120 V 277 277 V 347 347 V* UNV universal	DP dimming (0-10V) 1% - integral
Consult factory for other color temperatures		2ft min, 1 ft increment, 4 ft max stand alone. *System runs contain joiners - see page 3 For all other lengths and related outputs, please consult factory.	* Remote driver only.		Integral driver

CIRCUITS	MOUNTING	RS	REMOTE BATTERY (OPTIONAL)	CUSTOM (OPTIONAL)
		ORIENTATION		
+E(#) emergency circuit	MT mounting track for drywall and solid surfaces DF drywall flange DS drywall spackle flange SB9 surface TB 9/16 SBS surface screw slot t-bar	RS right angle surface	B(#) remote battery pack	C custom
Specify quantity 4' length min	Not available on 15/16 T-bars Please consult factory for power feed options available for your application.	See top of page for orientation	Remote only	Please specify

● [VIEW ALL ORIENTATION OPTIONS](#)


MOUNTING SIDE



LIGHT DISTRIBUTION

		asymmetric on step side	LUMENS %		lambertian on step side	LUMENS %
		asymmetric on flat side	50%		lambertian on flat side	50%
		asymmetric on step side	60%		lambertian on step side	40%
		lambertian on flat side	40%		asymmetric on flat side	60%

*See page 6 for photometry

	WALL				SURFACE
	HORIZONTAL		VERTICAL		
	DOWN	UP	LEFT	RIGHT	
FLAT MOUNT (F) (solid (SF) always on the flat side)	 Flat Wall Horizontal Down FWHD	NA	 Flat Wall Vertical Left FWVL	 Flat Wall Vertical Right FWVR	 Flat Surface FS
RIGHT ANGLE MOUNT (R) Step and Flat sides lit.	NA	NA	NA	NA	 Right Angle Surface RS
RIGHT ANGLE MOUNT (R) Step side lit.	NA	NA	NA	NA	 Right Angle Surface RS
STEP MOUNT (S) Step and Flat sides lit. (recommend lambertian (LS) on the step side)	 Step Wall Horizontal Down SWHD	NA	 Step Wall Vertical Left SWVL	 Step Wall Vertical Right SWVR	NA
STEP MOUNT (S) Flat side lit. (recommend lambertian (LS) on the step side)	 Step Wall Horizontal Down SWHD	NA	 Step Wall Vertical Left SWVL	 Step Wall Vertical Right SWVR	NA

(Note: These orientations help orient installation by the contractor. If you indicate an orientation in your product code it will be placed on the shop drawings)

● SPECIFICATIONS

CONSTRUCTION

Housing	Extruded aluminum (0.05" nominal) Up to 70% recycled content
End Cap	Cast aluminum
Interior Brackets	Die formed sheet steel (22 gauge)
Reflectors	White powder coated sheet steel (24 gauge)
Lenses	Extruded acrylic (0.070" nominal)

● ELECTRICAL

Emergency Remote emergency battery pack or emergency circuit optional.

Input Voltage 120V, 277V, 347V (remote), UNV.

i Incorporating these components may have limitations or affect the length of the luminaire, please contact factory for more details.

● LED SYSTEM

CRI	Minimum 80 or 90 color rendering index.
CCT	Choice of 2700K, 3000K, 3500K and 4000K color temperature with a great color consistency (within 3-step MacAdam ellipse). Both within fixture and fixture to fixture.
LED life	Minimum 50,000h with 85% of lumen maintenance in 25°C ambient temperature, in compliance with IES LM-80 testing measurements.
Thermal Management	Aluminum housing acting as the heat sink to maximize life.
Environment	Dry and damp rated in operating ambient temperatures of 0-40°C (32-104F).

● OPTICS

**BeWell Optics**

Axis' BeWell™ light guide technology provides multiple precise distribution options to deliver the many layers of light required in healthcare environments.

● SYSTEM (S#)

POSE linear systems, with the use of a strong profile, allow for a connection system of continuous runs.

Lengths of 2ft min, 1ft increments, 4 ft max stand alone, as well as custom lengths are available.

Runs of POSE that are greater than 4' in length are designated as systems (S#). This means that the run is comprised of a combination of sections to be assembled on site using our joining system. For more information on systems and joining, please refer to the POSE installation sheets available for download at www.axislighting.com.



● WARRANTY


Axis Lighting will warrant defective LEDs, boards, and drivers for 5 years from date of purchase. Warranty is valid if luminaire is installed and used according to specifications. If defective, Axis will send replacement boards or drivers at no cost along with detailed replacement instructions and instructions on how to return defective components to Axis.

Mounting flexibility, multiple application solutions

Choose from surface mount (MT) or recessed mount (DF) or spackle mount (DS) tracks.


SURFACE MOUNT TRACK (MT)

0.3" offset from surface




DRYWALL FLANGE (DF)*

Flush with surface



DRYWALL SPACKLE (DS)

Flush with surface



*min 5/8 thick drywall

● PHOTOMETRIC DATA




LUMENS %

asymmetric
on step side **60%**

lambertian
on flat side **40%**

Uplight 60%
750 lm/ft
Downlight 40% with Flush lens
500 lm/ft

PHOTOMETRIC CURVE



Lumen/ft up: 734 lm/ft
Lumen/ft down: 512 lm/ft
Total Lumens: 4985 lm (for 4ft)
Input Watts: 47.44 W
Efficacy: 105 lm/W

80 CRI shown. For 90 CRI, divide wattage by 0.8 and multiply efficacy by 0.8.

IES FILE: POSE-4-S-AS-LF-80-3500-W-120-DP-1.IES

TESTED ACCORDING TO IES LM-79-2008

CANDELA DISTRIBUTION

Vertical Angle	Horizontal Angles				
	0	22.5	45	67.5	90
0	700	700	700	700	700
5	697	699	701	701	701
15	672	677	682	685	686
25	626	632	639	644	645
35	558	564	572	578	579
45	470	477	483	490	490
55	368	373	378	383	383
65	254	258	263	266	267
75	137	141	146	148	149
85	38	38	39	39	38
90	1	9	17	21	22
95	34	60	75	80	80
105	220	258	306	347	366
115	466	561	681	797	851
125	585	730	946	1161	1256
135	599	728	921	1127	1218
145	586	679	804	927	982
155	575	635	701	765	791
165	570	603	633	659	668
175	567	576	586	594	596
180	567	567	567	567	567

ZONAL LUMENS

Zone	Lumens
0	
0-10	66
10-20	190
20-30	288
30-40	349
40-50	364
50-60	331
60-70	257
70-80	154
80-90	48
90	50
90-100	245
100-110	517
110-120	637
120-130	561
130-140	420
140-150	285
150-160	165
160-170	54
170-180	109
180	

LUMINANCE DATA (cd/m²)

Vertical Angle	Horizontal Angles		
	0	45	90
45	6870	7057	7161
55	6627	6806	6896
65	6215	6435	6529
75	5478	5844	5931
85	4446	4665	4488


● PHOTOMETRIC DATA



LUMENS %
lambertian on step side 50%
lambertian on flat side 50%

Uplight 50%
600 lm/ft
Downlight 50%
600 lm/ft

PHOTOMETRIC CURVE



Lumen/ft up: 585 lm/ft
Lumen/ft down: 599 lm/ft
Total Lumens: 4736 lm (for 4ft)
Input Watts: 47.45 W
Efficacy: 100 lm/W

80 CRI shown. For 90 CRI, divide wattage by 0.8 and multiply efficacy by 0.8.
IES FILE: POSE-4-S-LF-LS- 80-3500-W- 120-DP-1.IES

TESTED ACCORDING TO IES LM-79-2008

CANDELA DISTRIBUTION

Vertical Angle	Horizontal Angles				
	0	22.5	45	67.5	90
0	825	825	825	825	825
5	822	824	825	826	824
15	792	796	799	802	802
25	733	739	745	750	750
35	651	657	664	669	670
45	547	551	558	563	564
55	426	430	434	439	439
65	293	296	301	304	305
75	157	161	166	168	168
85	42	42	43	42	41
90	1	11	20	25	27
95	44	71	89	98	101
105	169	199	219	231	234
115	312	340	357	370	372
125	450	477	493	505	507
135	575	600	617	628	630
145	682	705	721	731	732
155	766	785	799	807	808
165	824	837	848	853	853
175	853	857	862	865	863
180	856	856	856	856	856

ZONAL LUMENS


Zone	Lumens
0	
0-10	78
10-20	223
20-30	338
30-40	409
40-50	425
50-60	386
60-70	299
70-80	180
80-90	57
90	51
90-100	156
100-110	280
110-120	373
120-130	419
130-140	409
140-150	343
150-160	229
160-170	81
170-180	109
180	

LUMINANCE DATA (cd/m²)

Vertical Angle	Horizontal Angles		
	0	45	90
45	7991	8147	8240
55	7676	7817	7907
65	7170	7352	7447
75	6277	6626	6723
85	4968	5094	4892

i All IES files are available for download at: www.axislighting.com


● PHOTOMETRIC DATA



LUMENS %
 asymmetric on step side 50%
 asymmetric on flat side 50%

Uplight 50%
 600 lm/ft
 Downlight 50%
 600 lm/ft

PHOTOMETRIC CURVE



Lumen/ft up: 654 lm/ft
 Lumen/ft down: 656 lm/ft
 Total Lumens: 5238 lm (for 4ft)
 Input Watts: 47.5 W
 Efficacy: 110 lm/W

80 CRI shown. For 90 CRI, divide wattage by 0.8 and multiply efficacy by 0.8.

IES FILE: POSE-4-S-AS-AF-80-3500-W-120-DP-1.1.IES

TESTED ACCORDING TO IES LM-79-2008

CANDELA DISTRIBUTION

Vertical Angle	Horizontal Angles				
	0	22.5	45	67.5	90
0	349	349	349	349	349
5	351	350	352	352	354
15	358	364	378	391	397
25	376	396	439	479	496
35	409	455	544	628	660
45	463	544	694	847	909
55	511	625	831	1050	1147
65	458	560	726	905	984
75	237	281	352	438	476
85	37	47	64	82	90
90	1	10	20	26	28
95	33	65	86	98	103
105	211	267	336	399	427
115	439	559	712	863	932
125	523	684	925	1167	1277
135	493	632	841	1057	1153
145	442	542	676	806	864
155	403	466	541	607	635
165	381	414	450	477	489
175	371	379	389	396	399
180	370	370	370	370	370

ZONAL LUMENS

Zone	Lumens
0	
0-10	34
10-20	108
20-30	197
30-40	310
40-50	454
50-60	592
60-70	557
70-80	303
80-90	67
90	54
90-100	245
100-110	510
110-120	606
120-130	498
130-140	342
140-150	212
150-160	113
160-170	36
170-180	109
180	

LUMINANCE DATA (cd/m²)

Vertical Angle	Horizontal Angles		
	0	45	90
45	6767	10139	13273
55	9195	14969	20649
65	11181	17746	24032
75	9467	14063	18997
85	4429	7603	10685