

Beam 2 LED


WALL MOUNT - DIRECT REGULAR LIT CORNER PATTERNS

Project _____

Type _____


Notes _____

*** Please see page 2 for example on how to specify various right angle patterns.**




TB2WDLEDPAT	R (11'X8')
PRODUCT ID	PATTERNS AND LENGTH

TOP VIEW - Rectangle Corner Pattern



TB2WDLEDPAT	FF(30)	OPR(120+60+50+120)
PRODUCT ID	PATTERNS AND LENGTH	CORNER DEGREES

TOP VIEW - Corner Pattern



TB2WDLEDPAT	U (9'X11'X11')
PRODUCT ID	PATTERNS AND LENGTH

TOP VIEW - Open Shape Corner Pattern

IMPORTANT! – all corner patterns must be submitted with drawings indicating dimensions and angles degree.

Ordering Guide




PRODUCT ID	PATTERNS AND LENGTH (SELECT ONE)	CORNER DEGREES (OPT.)	LUMENS/FT	CRI
TB2WDLEDPAT Beam 2 Wall Direct	S(L)* square shape (length)	FF(L) total pattern length	300 300 lm/ft - min	80 80 CRI
	R(LxL)* rectangular shape (length)		750 750 lm/ft - max for	90 90 CRI
	U(LxLxL)* U shape (length)		GZ, NW, ASO*	
	L(LxL)* L shape (length)		1000 1000 lm/ft - max	
	T(LxLxL)* T shape (length)			
	X(LxLxLxL)* X shape (length)			
	*Comes in 90 degree only.	FREE FORM for various angles. Minimum 2'.	Specify for FF option only. Please confirm corner degrees. Min 30° *Only available with SO, 0.25G, 1M, and UB direct shielding options	Outputs between listed min and max are available. * 750 lm/ft max. only for GZ, NW and ASO. Consult factory for outputs outside of the listed range.

COLOR TEMP. (choose one)	SHIELDING DIRECT	SPECIFY LENGTH	FINISH	VOLTAGE
27 2700 K TW2750 2700-5000 K - Tunable White	SO spotless lens	NL nominal	AP aluminum paint	120 120V
30 3000 K TW2765 2700-6500 K - Tunable White	BFBL black flat blade louver	EX exact	W white	277 277V
35 3500 K BTW3527 3500-2700 K - Tunable BIOS	WFBL white flat blade louver		BLK black	347 347V
40 4000 K BTW4027 4000-2700 K - Tunable BIOS	GFBL grey flat blade louver		C custom	UNV universal
B30 3000 K - BIOS*	0.25G 0.25" Glo lens			DC low voltage*
B35 3500 K - BIOS*	UB ultra blend lens			
B40 4000 K - BIOS*	1M StepLens , lum. end cap			
	ASO asymmetric, flush only			
	NW narrow, flush only			
	GZ graze, flush only			
Consult Axitone technical sheet for more information on color technology. *Consult BIOS guide for more information on BIOS technology				* Only available with POE drivers.

DRIVER	CIRCUITS	BATTERY	IC CONTROLS (OPTIONAL)	CUSTOM (OPTIONAL)
DP dimming (0-10V) 1%	1 1 circuit	B(#) battery pack	DS(#) daylight sensor	C custom
LT(#) Lutron*	2 2 circuits	4' sections	OS(#) occupancy sensor	
BI bi-level dimming	+E(#) emergency circuit *		DOS(#) daylight & occupancy sensor	
O(#) other**	+NL(#) night light circuit *		EN(#) Enlighted integral *	
DPB(STC) dimming (0-10V) 1% with BIOS*	+GTD(#) generator transfer device *		ENR(#) Enlighted remote *	
DPB(DYN) Bio-dimming™ 100%-81% with BIOS*			WC(#) wireless control dimming	
TW(#) tunable white drivers*				
POE(#) POE drivers*				
* Specify system ** Please consult factory	* Specify quantity	Requires 120V or 277V Please consult factory	* Please consult factory See integrated controls guide for more details.	Please specify


How to Specify 90 degree Corners and Patterns

Defining R - Rectangular shape




Note: The first number will always define the width, the second - the length.

Defining L shape




Defining U shape




Note: The first number will always define the right arm length, the second - the width, and the third - the left arm length.

Defining T shape




Note: The first number will always define the width, the second - the bottom arm length, and the third - the top arm length.

Defining S - Square shape



Note: The number will define the width. (All sides are the same length).

Defining X shape



Note: The first number will define length of the left arm, the second - the arm length to the right from the first, and so on until the 4th arm.

● LIT CORNER FEATURES


The Lit Corner system allows continuous illumination all the way through the corner section

To optimize corner illumination, lit corners are created as integral components of the linear sections. Linear sections have mitered ends that connect to corresponding mitered ends of neighboring linear sections.

Illuminated Corners are more complex. Because the corner is fully illuminated, the corner is not independent of the straight sections, but integrated into the straight segment's housing. The corner is mitered, allowing a seamless line of light.

Regular Illuminated Corner - A fully illuminated corner that lies on the same plane. There are two corner options available for Regular Lit Corners: **Open Shape Corner** and **Closed Shape Corner**

TIP: Provide sketches illustrating corner types and locations required.



ELECTRICAL

Lutron driver	LDE1 - Hi-lume 1% EcoSystem with Soft-on, Fade-to-Black
Other drivers**	DALI - Digital Addressable Lighting Interface DMX - Digital Multiplex Xitanium SR - For wireless sensor
BIOS DPB drivers*	STC - BIOS control 0-10V with static spectrum and BIOS SkyBlue enabled from 100% to 1%. DYN - BIOS control 0-10V with dynamic spectrum and BIOS SkyBlue® with Bio-Dimming™, which changes spectral qualities by removing the SkyBlue component when dimming from 100% to 81%, while light output remains relatively constant; bio-dimming reduces CCT to 2700K. Dimming from 80% to 1% will then reduce light output.
Tunable White TW drivers*	DALIDT6 - DALI Type 6 (Two DALI Addresses) DALIDT8 - DALI Type 8 (One DALI Address)
Power over Ethernet POE drivers*	MOLEX IGOR SMARTENGINE O - Other (Consult factory)
Emergency	Integral emergency battery pack or emergency circuit optional.
Input Voltage	120V, 277V, 347V, UNV, DC.
Flex Whip	Shipped in a separate box for contractors to install


*Choose driver from available options.

i Incorporating these components may have limitations or affect the length of the luminaire. Please contact factory for more details.

WARRANTY

Limited 5-year warranty is available. Warranty is valid provided luminaires are installed and used according to specifications. For full terms and conditions, please consult warranty section at axislighting.com.

APPROVALS

Certified to UL and CUL standards 
Meets NYC requirements
Meets ADA requirements.
Suitable for damp locations.

LED SYSTEM

CRI	Minimum 80 or 90 color rendering index.
CRI BIOS	Minimum 80 color rendering index with R9>75 for all CCTs.
CCT Single Color	Choice of 2700K, 3000K, 3500K and 4000K color temperature with a great color consistency (within 3-step MacAdam ellipse). Both within fixture and fixture to fixture.
CCT BIOS	BIOS Static (STC) Choice of 3000K, 3500K and 4000K. BIOS SkyBlue® Dynamic (DYN) Choice of 3000K, 3500K, and 4000K with Bio-Dimming™ BIOS Tunable White (BTW) Choice of 4000-2700K and 3500-2700K; does not use a bio-dimmer, it uses TW drivers, which allow independent control of CCT and intensity; e.g., BTW4027 provides combined SkyBlue + white light at 4000K, SkyBlue is removed at 2700K. Light output can be adjusted for each CCT. Consult BIOS guide for more information on BIOS technology.
CCT Axitune Systems	Consult Axitune technical sheet for more information on color technology.
LED life	Minimum 50,000h with 85% of lumen maintenance in 25°C ambient temperature, in compliance with IES LM-80 testing measurements.
Thermal Management	Aluminum housing acting as the heat sink to maximize life.
Environment	Dry and damp rated for indoor use only in operating ambient temperatures of 0-40°C (32-104°F).



A large grid of squares, intended for drawing corner patterns. The grid is composed of 30 columns and 30 rows of squares, providing a space for technical drawings.