





SIDE VIEWS (ALL AVAILABLE SIZES)



Project _____

Type _____

Notes _____



Also available as a Stand Alone Pendant, please refer to [CTPD.SPEC spec sheet](#)

SPECIFICATIONS TABLE

AXISTRAK™ TOTAL POWER PER SEGMENT	60 W
UNIT POWER CONSUMPTION	20 W
NOMINAL WEIGHT (36" CYLINDER)*	4.02 lbp / 1.82 kg
* Shown for 36" size. See page 2 for all sizes.	

Please specify location of spotlights on system configuration drawing.

Ordering Guide

TDCTP						90		NMP		SCR				
PRODUCT ID			LENGTH		BEAM ANGLE	NOM. LUMENS	CRI		COLOR TEMP.		HOUSING FINISH	TRIM FINISH		
TDCTP	Chime Taper Pendant	1.5	1.5'	NB	narrow	HI	90	90 CRI	27	2700K	NMP	natural maple	SCR	silver chrome
		2	2'	MB	medium*				30	3000K				
		3	3'	WB	wide				35	3500K				
									40	4000K				
					* Default option.	* See page 4-5 Photometric Data for Total lumen output.								

MOUNTING		CONTROLS				MOUNTING FINISH		PENDANT CABLE LENGTH				
AXT	AxisTrak™	DP	integral driver 0-10V dimming (1%) - wired*			BLK	black	TLA(L)	track length adjustable (specify length between 6" and 140" – includes 18" of additional internal cable for on-site adjustment)			
		DALIDT6	integral driver DALI 2.0 Type 6 - wired**			AP	aluminum paint					
		EP	integral driver for Empower wireless with integral sensor / control module***			W	white					
						C	custom					
		* Available with multicircuit wiring.				AxisTrak™ adapters only available in white or black.		Special swag mounting hardware available, such as swag rail and/or swag hooks. See details on page 2.				
		** Must use IMWD controls option with SFF framework, and DALIDT6CV(#) controls option with AxisTrak insert.						To order other Swag mounting accessories, such as Rails and Hooks, see Swag Accessories for Pendants Spec sheet.				
		*** Must use IMWEP controls option with SFF framework, and EPCV(#) controls option with AxisTrak insert.										

CONSTRUCTION

- Wood housing** Solid maple construction. Wood varnish - natural color.
- Metal housing** Extruded aluminum.
- Optic holder** Die cast aluminum with chrome or painted metal finish. Heat sink construction holds LED array and regressed acrylic TIR optic.
- Mounting** Concealed cable gripper for easy suspension length adjustment.

LED SYSTEM

- CRI** Minimum 90 color rendering index
- CCT** 3000K color temperature with a great color consistency (within 3-step MacAdam ellipse).
- LED life** Minimum 50,000h with 85% of lumen maintenance in 25°C ambient temperature, in compliance with IES LM-80 testing measurements.
- Thermal Management** Aluminum housing acting as the heat sink to maximize life.

ELECTRICAL

- DP** Integral 0-10v 1% dimming low voltage driver (48V)
- DALIDT6** Integral Dali 2.0 D4i type 6 low voltage driver (48V)
- EP** Integral Dali 2.0 D4i interface to connect to wireless/sensor node on the AxisTrack (48V)
- i** Incorporating these components may have limitations or affect the length of the luminaire, please contact factory for more details.


FINISH

- Housing** Solid maple construction. Wood varnish - natural color.
- Trims** Silver chrome.


APPROVALS

Certified to cULus standards.  All Decoratives, Pendants, and Spotlights certified under UL2108.


BEAM SPREADS



MOUNTING DIMENSIONS



SWAG MOUNTING DETAILS



To get more details and order swag mounting hardware please see [Swag Accessories for Pendants Spec sheet](#).


WEIGHT

PRODUCT	SIZE	WEIGHT(lbp)	WEIGHT (kg)
Chime Taper	18"	2.01	0.91
	24"	2.66	1.20
	36"	3.95	1.79

WARRANTY

Limited 5-year warranty is available. Warranty is valid provided luminaires are installed and used according to specifications. For full terms and conditions, please consult warranty section at [axislighting.com](#).

SPECIFICATION EXAMPLE FOR USE IN STENCILFLEX®




Here is how to specify Within an AxisTrak™

EXAMPLE CODE

- 1) FRAMEWORK: SFF-L(37)-LC90(2)+LC902ST55(2)+T90(2)-BLK-120-IMW-1-CA(36)-RC
- 1.1) SPOT LIGHTS ON CURVE SEGMENT: TDST55-MB-1600-90-35-BLK-LC902ST55 (QTY. 4)
- 2.2) AXISTRAK™ INSERT: SFLDAXT-5-120-DPCV-BLK
SFLDAXT-7-120-DPCV-BLK
- 3) TRACK ELEMENTS & DECORATIVES: TDCTP-2-MB-350-90-30-NMP-SCR-AXT-DP-BLK-TLA (Qty. 2)

● PHOTOMETRIC DATA

Narrow 15° beam



Total Lumens: 1765 lm
Input Watts: 20 W
Efficacy: 88 lm/W

IES FILE: SFL3CxP-x-NB-1700-90-30.ies
 TESTED ACCORDING TO IES LM-79-2008

CANDELA DISTRIBUTION

Vertical Angle	Horizontal Angles				
	0	22.5	45	67.5	90
0	27977	27977	27977	27977	27977
5	17730	17635	17794	18149	18862
15	892	873	874	908	988
25	170	166	167	169	180
35	57	56	56	57	62
45	18	18	18	19	21
55	5	5	5	5	7
65	1	1	1	1	2
75	0	0	0	0	0
85	0	0	0	0	0
90	0	0	0	0	0


ZONAL LUMENS

Zone	Lumens
0	
0-10	1327
10-20	381
20-30	88
30-40	37
40-50	15
50-60	5
60-70	1
70-80	0
80-90	0
90	

LUMINANCE DATA (cd/m²)

Vertical Angle	Horizontal Angles		
	0	45	90
45	7926	7919	9277
55	2760	2622	4026
65	665	432	1334
75	47	47	44
85	235	228	217

Medium 35° beam



Total Lumens: 1824 lm
Input Watts: 20 W
Efficacy: 91 lm/W

IES FILE: SFL3CxP-x-MB-1700-90-30.ies
 TESTED ACCORDING TO IES LM-79-2008

CANDELA DISTRIBUTION

Vertical Angle	Horizontal Angles				
	0	22.5	45	67.5	90
0	3911	3911	3911	3911	3911
5	3871	3846	3843	3839	3832
15	2840	2847	2845	2831	2821
25	1052	1063	1067	1055	1032
35	198	200	201	200	197
45	39	39	40	40	39
55	10	10	10	10	10
65	3	3	3	3	3
75	0	0	0	0	0
85	0	0	0	0	0
90	0	0	0	0	0

ZONAL LUMENS

Zone	Lumens
0	
0-10	355
10-20	767
20-30	506
30-40	148
40-50	35
50-60	10
60-70	3
70-80	0
80-90	0
90	


LUMINANCE DATA (cd/m²)

Vertical Angle	Horizontal Angles		
	0	45	90
45	17065	17418	17357
55	5367	5455	5558
65	1853	1948	2031
75	72	71	70
85	460	435	431

i All IES files are available for download at: www.axislighting.com

PHOTOMETRIC DATA

Wide 55° beam



Total Lumens: 1653 lm
Input Watts: 20 W
Efficacy: 83 lm/W

IES FILE: SFL3CxP-x-WB-1700-90-30.ies
TESTED ACCORDING TO IES LM-79-2008

CANDELA DISTRIBUTION					
Vertical Angle	Horizontal Angles				
	0	22.5	45	67.5	90
0	2369	2369	2369	2369	2369
5	2279	2270	2267	2270	2270
15	2079	2058	2040	2037	2026
25	1428	1413	1380	1356	1389
35	280	305	315	350	383
45	32	33	33	33	35
55	11	12	12	12	13
65	3	4	4	4	4
75	0	0	0	0	0
85	0	0	0	0	0
90	0	0	0	0	0

ZONAL LUMENS	
Zone	Lumens
0	
0-10	213
10-20	571
20-30	616
30-40	229
40-50	30
50-60	11
60-70	4
70-80	0
80-90	0
90	

LUMINANCE DATA (cd/m²)			
Vertical Angle	Horizontal Angles		
	0	45	90
45	14034	14581	15210
55	6008	6699	6805
65	2534	2850	2827
75	89	82	78
85	656	595	542