


Ordering Guide (fill out green boxes to complete code)

STSZ	NI	DSO(,)		BH(6)					
PRODUCT ID		LENGTH & NOM. LUMENS/FT - DIRECT		HUB QUANTITY SERIES B		CRI	COLOR TEMP.	FINISH	
STSZ Stencil SoftZone Hexagon Pendant Direct	NI no indirect	DSO(H2, lumen) direct spotless lens 2 ft	200 200 lm/ft	BH(6) Hex Hub (120°)	80 80 CRI	27 2700 K	BLK black		
		DSO(H3, lumen) direct spotless lens 3 ft	300 300 lm/ft		90 90 CRI	30 3000 K	W white		
		DSO(H4, lumen) direct spotless lens 4 ft	400 400 lm/ft			35 3500 K	RAL(#) pick your RAL*		
						40 4000 K	C(#) custom		
Segment length from 2' to 4' continuous.								*Specify RAL#	

VOLTAGE	DRIVER	CIRCUITS	MOUNTING/SUSPENSION	CANOPY	BATTERY - REMOTE (OPT.)
120 120 V 277 277 V UNV universal DC low voltage*	DP integral 0-10V driver dimming (1%)* POE(MOLEX) POE Molex driver POE(IGOR) POE IGOR driver POE(SMARTENGINE) POE Smartengine driver	1 1 circuit 2 2 circuits +E(#) emergency circuit * +NL(#) night light circuit	CA(L) drywall+cable length (36" std.)* CT9(L) TB/TG 9/16+cable length (36" std.)* CT15(L) TB/TG15/16+cable length (36" std.)* CTS(L) screw slot+cable length (36" std.)* CASL(L) drywall cable sloped ceiling*	RC round canopy SC square canopy	B(#) remote battery pack
* Only available with POE drivers.	* Only integral 0-10V driver available	* Specify quantity	See Mounting kit guide for full specification code. *Specify length in inches.	White canopy standard	Remote only Please consult factory

Ordering Guide - SoftZone Panels

Panel ID (Color, QTY)		
PANEL ID	SOFTZONE PANEL COLOR	PANEL QUANTITY
HE2 2' hexagon (full)	See appendix 1 for available colors.	1 panel quantity - for HE2 (2' hexagon) only
HET3 3' hexagon (triangle segment)		6 panel quantity - for HET3 and HET4
HET4 4' hexagon (triangle segment)		(3' and 4' hexagons)



* See Appendix 2 for more information.



APPENDIX

APPENDIX 1: SOFTZONE PANEL COLOR PALETTE

STANDARD PANEL COLOR PALETTE

WITH MATCHING HOUSING COLORS



EXTENDED PANEL COLOR PALETTE

Available per request. Consult factory for details.



APPENDIX 2: SOFTZONE PANEL CARE AND WARRANTY

● CLEANING PROTOCOL



NOTE: Easy to clean. Made from polyester fill with natural anti-microbial properties.



Periodic dusting with vacuum or dry cloth recommended.



For stain removal, use a small amount of soap or detergent on a wet cloth.



For added disinfection, use bleach solution (5 tablespoons per Gallon of water), spray onto surface and gently wipe to spread all over.

● APPROVALS



Certified to UL and CSA standards.  Suitable for damp locations.

FIRE SAFETY: Class A Fire Rated as per ASTM E84.
Flame Spread Index: 5
Smoke Development Index: 110

● SOFTZONE® WARRANTY

All SoftZone® Acoustic panels are guaranteed for 1 year (warranty period) from date of shipment from our factory. Defective products will be repaired or replaced at the discretion of Axis Lighting provided a written claim is made within the warranty period.

Exclusions of SoftZone® Warranty:

- Normal wear and tear (scratches, direct sunlight, etc.).
- Products that have been modified, improperly installed, used in conditions or for purposes other than which they were intended.