

## Ordering Guide (fill out green boxes to complete code)

STSZ		NI	D	so ( ,	)				BT(3)						
PRODUCT ID			LENGTH	LENGTH & NOM. LUMENS/FT - DIRECT				HUB QUANTITY SERIES B		CRI		COLOR TEMP.		FINISH	
STSZ	Stencil SoftZone	NI no indirect	DSO(T2, lumen)	direct spotless I	lens 2 ft 2	200 2	200 lm/ft	BT(3)	Triangle Hub (60°)	80	80 CRI	27	2700 K	BLK	black
	Triangle Pendant		DSO(T3, lumen)	direct spotless I	lens 3 ft 3	<b>300</b> 3	300 lm/ft		-	90	90 CRI	30	3000 K	w	white
	Direct		DSO(T4, lumen)	direct spotless I	lens 4 ft 4	100 4	400 lm/ft					35	3500 K	RAL(#)	pick your RAL*
												40	4000 K	C(#)	custom
			Segment length 2', 3', ar	Segment length 2', 3', and 4' available.										* Specify RAL#	


VOLTAGE		DRIVER		CIRCUITS		MOUNTING/SUSPENSION			CANOPY		BATTERY - REMOTE (OPT.)	
120	120 V	DP	integral 0-10V driver	1	1 circuit	CA(L)	drywall+cable length (36" std.)*	RC	round canopy	B(#)	remote battery pack	
277	277 V		dimming (1%)*	2	2 circuits	CT9(L)	TB/TG 9/16+cable length (36" std.)*	SC	square canopy			
UNV	universal	POE(MOLEX)	POE Molex driver	+ E(#)	emergency circuit *	CT15(L)	TB/TG15/16+cable length (36" std.)*					
DC	low voltage*	POE(IGOR)	POE IGOR driver	+NL(#)	night light circuit	CTS(L)	screw slot+cable length (36" std.)*					
		POE(SMARTENGINE)	POE Smartengine			CASL(L)	drywall cable sloped ceiling*					
			driver									
		* Only integral 0-10V driver available							White canopy standard		Remote only	
drivers.						Specify length in inches.				Please consult factory		

### **Ordering Guide - SoftZone Panels**

	tr F	(				
	PANEL ID	SOFTZONE PANEL COLOR	PANEL QUANTITY			
TR3	2' triangle- 60° only 3' triangle- 60° only 4' triangle- 60° only	See appendix 1 for available colors.	1	panel quantity		







Refer to specification sheets for complete details, and other design ideas. Note that only options shown above qualify as part of Creative Collection. Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Refer to our web site axislighting.com for the latest product information.

© 2016 Axis Lighting Inc. 1.800.263.2947 [T] 514.948.6272



# **APPENDIX 1: SOFTZONE PANEL COLOR PALETTE**

## **STANDARD PANEL COLOR PALETTE**

## **EXTENDED PANEL COLOR PALETTE**

### WITH MATCHING HOUSING COLORS

Available per request. Consult factory for details.








# **APPENDIX 2: SOFTZONE PANEL CARE AND WARRANTY**

### • CLEANING PROTOCOL



NOTE: Easy to clean. Made from polyester fill with natural antimicrobial properties.



For stain removal, use a small amount of soap or detergent on a wet cloth.

For added disinfection, use bleach solution (5 tablespoons per Gallon of water), spray onto surface and gently wipe to spread all over.

### APPROVALS

Certified to UL and CSA standards. Control of the standards. Control of the standards. Control of the standards of the standa

FIRE SAFETY: Class A Fire Rated as per ASTM E84. Flame Spread Index: 5 Smoke Development Index: 110

#### • SOFTZONE® WARRANTY

All SoftZone<sup>®</sup> Acoustic panels are guaranteed for 1 year (warranty period) from date of shipment from our factory. Defective products will be repaired or replaced at the discretion of Axis Lighting provided a written claim is made within the warranty period.

### Exclusions of SoftZone® Warranty:

- Normal wear and tear (scratches, direct sunlight, etc.).
- Products that have been modified, improperly installed, used in conditions or for purposes other than which they were intended.

