





Project \_\_\_\_\_

Type \_\_\_\_\_


Notes \_\_\_\_\_




## Framework and inserts sold separately



LattiX 2x2 24" Cell Grid  
Shown with 5'x5' framework



LattiX 3x2 24" Cell Grid  
Shown with 8'x6' framework



LattiX 3x3 24" Cell Grid  
Shown with 7'x7' framework



\* See page 4 for more information.


## Ordering Guide

SFLT <sup>X</sup>						LTX(	
-------------------	--	--	--	--	--	------	--

See detail dimensions on page 3  
! Please ensure to order framework that matches these dimensions separately (see Framework (SFF) spec sheet).

! Please ensure that your hardware finish matches your framework finish selection (see Framework (SFF) spec sheet).  
\* Wood finishes available see page 3 for recommended color codes.

SPECIFICATION EXAMPLE



Follow ordering guide to specify

EXAMPLE CODE

**FRAMEWORK:** SFF-L(35)-L90(4)+T90(2)-W-120-IMW-1-CA(36)-RC  
**INDIRECT INSERT:** SFLISL-5-500-80-35-120-DP-W  
**OTHER INSERTS:** ...  
**TRACK DECORATIVES:** ...  
**LATTIX:** SFLT X-5-W-FLT(07,2)

## LATTIX FELT COLOR PALETTE

### 9MM COLORS




### 9MM TEXTURES




## LATTIX SIZES WITH AVAILABLE STENCILFLEX FRAMEWORK

### SIZE 5




5 ft x 5 ft  
Framework

### SIZE 6




6 ft x 6 ft  
Framework

### SIZE 6R




6 ft x 8 ft  
Framework

### SIZE 7




7 ft x 7 ft  
Framework

### SIZE 7.5



7.5 ft x 7.5 ft  
Framework

### SIZE 8



8 ft x 8 ft  
Framework

## ● CONSTRUCTION

<b>Structure</b>	Extruded aluminum
<b>Panel</b>	100% polyester containing at least 40% of recycled PET plastic

## ● CLEANING PROTOCOL



### PET Felt

PET felt is manufactured with 60% recycled material. The process used to create PET felt often results in a heathered effect where multiple tones are present. Slight variations in color should be expected when using this sustainable material.



### Dust + Debris Removal

A vacuum or air compressor should be used as needed to remove any dust or debris that may have accumulated. Nozzel attachment tools for vacuums are especially useful when cleaning between baffles.



### Stain Removal

In instances where a wet spill occurs, blot stain immediately with a clean, dry cloth. Do not rub paper products such as facial tissue on to the material, as this could result in paper particulate being rubbed in to the material.

In most cases, a simple solvent of soap and water can be used to remove stains. For more severe instances, household bleach is effective at removing stains. Due to the dyeing process of the fibers, PET felt is able to retain its colorfastness when cleaned with bleach.

Material should air-dry - no heat should be used to speed the drying process.



### Cleaning

If surfaces are dirty, they should be cleaned using a detergent or soap and water prior to disinfection.



### Disinfecting

For disinfection, most common EPA-registered household disinfectants should be effective.

- A list of products that are EPA-approved for use against the virus that causes COVID-19 is available [here](#).
- Additionally, diluted household bleach solutions (at least 1000ppm sodium hypochlorite) can be sprayed on
- Prepare a bleach solution by mixing 5 tablespoons (1/3rd cup) bleach per gallon of water
- Bleach solutions will be effective for disinfection up to 24 hours.

## ● LATTIX™ WARRANTY

AXIS supports its products with warranties that provide comprehensive coverage. Products are rigorously tested and certified to meet stringent industry standards. In the unlikely circumstances that a product requires servicing, AXIS responds promptly.

AXIS acoustic products are warranted for three years from the final invoice date of the order.

### Qualifications:

- Warranty applies only to the original owner/purchaser of the product, and is not transferrable
- All claims under this warranty must be communicated to a local authorized service agent or distributor of AXIS products
- AXIS reserves the right to determine the cause of the claim and to address any claims under this warranty
- Financial reimbursement will not be paid for any work carried out by an unauthorized third party
- The express warranties contained herein are in lieu of all warranties for products using adhesives

### Exclusions of Warranty:

- Normal wear and tear (scratches, etc.) and/or user abuse
- Any damage resulting from moisture, heat, or direct sunlight
- Modifications made to product after initial shipment

## ● APPROVALS

Certified to cULus standards.



**FIRE SAFETY:** Class A Fire Rated as per ASTM E84.  
Flame Spread Index: 5  
Smoke Development Index: 110