



Refer to axislighting.com for complete fixture details, IES files, and installation instructions

Project _____

Type _____

Notes _____

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI

NOMINAL LUMEN OUTPUT		INPUT WATTS*	EFFICACY	SHIELDING I/D
UPLIGHT	DOWNLIGHT			
1100 lm/ft	1000 lm/ft	16.8 W/ft	125 lm/W	SO/SO
1100 lm/ft	750 lm/ft	15.7 W/ft	128 lm/W	SO/ASO
1100 lm/ft	1000 lm/ft	18.2 W/ft	116 lm/W	SO/BW
1100 lm/ft	750 lm/ft	15.7 W/ft	122 lm/W	SO/NW
1100 lm/ft	750 lm/ft	15.7 W/ft	121 lm/W	SO/GZ
1100 lm/ft	750 lm/ft	15.7 W/ft	122 lm/W	SO/WW
1100 lm/ft	1000 lm/ft	16.0 W/ft	131 lm/W	BW/SO
1100 lm/ft	750 lm/ft	14.9 W/ft	128 lm/W	BW/ASO
1100 lm/ft	1000 lm/ft	17.4 W/ft	121 lm/W	BW/BW
1100 lm/ft	750 lm/ft	14.9 W/ft	128 lm/W	BW/NW
1100 lm/ft	750 lm/ft	15.0 W/ft	127 lm/W	BW/GZ
1100 lm/ft	750 lm/ft	15.0 W/ft	128 lm/W	BW/WW



Ordering Guide

TB2DILED	PRODUCT ID	NOM. LUM/FT UP	NOM. LUM/FT DOWN	CRI	COLOR TEMP.	SHIELDING INDIRECT	SHIELDING DIRECT
TB2DILED	Beam2 - Pendant Direct/Indirect LED	300 300 lm/ft-Min 1100 1100 lm/ft-Max	300 300 lm/ft - min 750 750 lm/ft - max for GZ, NW, WW, ASO* 1000 1000 lm/ft - max	80 80 CRI	30 3000 K 35 3500 K 40 4000 K	SO spotless lens BW batwing	SO spotless lens ASO Asymmetric BW Batwing NW Narrow GZ Graze flush WW Wallwash flush
		Outputs between listed min and max are available.	Outputs between listed min and max are available. * 750 lm/ft max. only for GZ, NW, WW and ASO.				

LENGTH (FT)	FINISH	VOLTAGE	DRIVER	CIRCUITS	MOUNTING/SUSPENSION
4 4' 5 5' 8 8' 12 12' S(L) System Run	W white BLK black* AP aluminum paint*	120 120 V 277 277 V 347 347 V UNV universal	DP dimming (0-10V) 1%	1 1 circuit 2 2 circuits +E(##) emergency circuit*	CA(##) drywall+cable length (36" std.) CT9(##) TB/TG 9/16+cable length (36" std.) CT15(##) TB/TG15/16+cable length (36" std.) CTS(##) screw slot+cable length (36" std.) SA(##) drywall+stem length <48" (18" std.) CASL(##) drywall cable sloped ceiling SASL(##) drywall stem sloped ceiling See Mounting kit guide for full specification code. White canopy standard
Available in 1' increments.	*Additional 5 working days required.			*Specify quantity	

BATTERY (OPTIONAL)	
B(##)	battery pack (integral)
Minimum 5ft; Not available with 347V Please consult factory.	

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.