



Refer to [axislighting.com](http://axislighting.com) for complete fixture details, IES files, and installation instructions

Project \_\_\_\_\_

Type \_\_\_\_\_

Notes \_\_\_\_\_

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI

NOMINAL LUMEN OUTPUT		INPUT WATTS*	EFFICACY	SHIELDING I/D
UPLIGHT	DOWNLIGHT			
1200 lm/ft	1100 lm/ft	17.5 W/ft	132 lm/W	SO/SO
1200 lm/ft	1000 lm/ft	18.1 W/ft	125 lm/W	SO/ASO
1200 lm/ft	1000 lm/ft	18.1 W/ft	125 lm/W	SO/NW
1200 lm/ft	1000 lm/ft	17.9 W/ft	126 lm/W	SO/GZ

\* Based on a 4 foot flush luminaire using one driver



Ordering Guide

TB3WDILED													
PRODUCT ID		NOM. LUM/FT UP		NOM. LUM/FT DOWN		CRI		COLOR TEMP.		SHIELDING INDIRECT		SHIELDING DIRECT	
TB3WDILED	BEAM3 - Wall	300	300 lm/ft-Min	300	300 lm/ft - min	80	80 CRI	30	3000 K	SO	spotless lens	SO	spotless lens
	Direct/Indirect LED	1200	1200 lm/ft-Max	1000	1000 lm/ft - max for			35	3500 K			ASO	Asymmetric
				GZ, NW, ASO*				40	4000 K			NW	Narrow
				1100	1100 lm/ft - max							GZ	Graze
		Outputs between listed min and max are available.		Outputs between listed min and max are available. * 1000 lm/ft max. only for GZ, NW and ASO.									

LENGTH (FT)	FINISH	VOLTAGE	DRIVER	CIRCUITS	BATTERY (OPTIONAL)
4 4' 5 5' 6 6' 8 8' 12 12' S(L) System Run	W white BLK black* AP aluminum paint*	120 120 V 277 277 V 347 347 V UNV universal	DP dimming (0-10V) 1%	1 1 circuit 2 2 circuits +E(#) emergency circuit*	B(#) battery pack (integral)
Available in 1' increments.	* Additional 5 working days required.			*Specify quantity	Minimum 5ft. Not available with 347V Please consult factory

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.