



Refer to axislighting.com for complete fixture details, IES files, and installation instructions

Project _____

Type _____

Notes _____

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI

NOMINAL LUMEN OUTPUT	INPUT WATTS*	EFFICACY	SHIELDING
1100 lm/ft	8.8 W/ft	125 lm/W	SO
1100 lm/ft	9.1 W/ft	122 lm/W	BW
1000 lm/ft	9.3 W/ft	114 lm/W	GZ
1000 lm/ft	9.5 W/ft	112 lm/W	NW
1000 lm/ft	9.4 W/ft	113 lm/W	WW
1000 lm/ft	9.4 W/ft	113 lm/W	ASO

* Based on a 4 foot flush luminaire using one driver



Ordering Guide

TB3SLED													
PRODUCT ID		NOM. LUM/FT DOWN		CRI	COLOR TEMP.	SHIELDING	LENGTH (FT)	FINISH					
TB3SLED	BEAM3 - Surface LED	300	300 lm/ft - min	80	80 CRI	30	3000 K	SO	spotless lens	4	4'	W	white
		1000	1000 lm/ft - max for GZ, NW, WW, ASO.*			35	3500 K	ASO	Asymmetric	5	5'	BLK	black*
						40	4000 K	BW	Batwing	6	6'	AP	aluminum paint*
								NW	Narrow	8	8'		
		1100	1100 lm/ft - max			GZ	Graze	12	12'				
						WW	Wallwash	S(L)	System Run				
		Outputs between listed min and max are available. * 1000 lm/ft max. only for GZ, NW,WW and ASO.				*Lens options use spotless lens. Choose only one of the options above.		Available in 1' increments.		* Additional 5 working days required.			

VOLTAGE	DRIVER	CIRCUITS	MOUNTING	BATTERY (OPTIONAL)
120 120 V	DP dimming (0-10V) 1%	1 1 circuit	SB9 surface TB/TG 9/16	B(##) battery pack (integral)
277 277 V		2 2 circuits	SB15 surface TB/TG 15/16	
347 347 V		+E(##) emergency circuit*	SBS surface screw slot t-bar	
UNV universal			S surface drywall ceiling	
			SC surface solid ceiling	
		*Specify quantity		Minimum 5ft; Not available with 347V Please consult factory

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.