



Refer to axislighting.com for complete fixture details, IES files, and installation instructions

Project _____

Type _____

Notes _____

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI

NOMINAL LUMEN OUTPUT		INPUT WATTS*	EFFICACY	SHIELDING I/D
UPLIGHT	DOWNLIGHT			
1200 lm/ft	1100 lm/ft	17.5 W/ft	132 lm/W	SO/SO
1200 lm/ft	1000 lm/ft	18.1 W/ft	125 lm/W	SO/ASO
1200 lm/ft	1100 lm/ft	17.7 W/ft	130 lm/W	SO/BW
1200 lm/ft	1000 lm/ft	18.1 W/ft	125 lm/W	SO/NW
1200 lm/ft	1000 lm/ft	17.9 W/ft	126 lm/W	SO/GZ
1200 lm/ft	1000 lm/ft	18.1 W/ft	125 lm/W	SO/WW
1200 lm/ft	1100 lm/ft	16.8 W/ft	136 lm/W	BW/SO
1200 lm/ft	1000 lm/ft	17.5 W/ft	130 lm/W	BW/ASO
1200 lm/ft	1100 lm/ft	17.1 W/ft	135 lm/W	BW/BW
1200 lm/ft	1000 lm/ft	17.5 W/ft	129 lm/W	BW/NW
1200 lm/ft	1000 lm/ft	17.5 W/ft	130 lm/W	BW/GZ
1200 lm/ft	1000 lm/ft	17.5 W/ft	130 lm/W	BW/WW

* Based on a 4 foot flush luminaire using one driver



Ordering Guide

TB3DILED						
PRODUCT ID	NOM. LUM/FT UP	NOM. LUM/FT DOWN	CRI	COLOR TEMP.	SHIELDING INDIRECT	SHIELDING DIRECT
TB3DILED BEAM3 - Pendant Direct/Indirect LED	300 300 lm/ft-Min 1200 1200 lm/ft-Max	300 300 lm/ft - min 1000 1000 lm/ft - max for GZ, NW, WW, ASO* 1100 1100 lm/ft - max	80 80 CRI	30 3000 K 35 3500 K 40 4000 K	SO spotless lens BW batwing	SO spotless lens ASO Asymmetric BW Batwing NW Narrow GZ Graze WW Wallwash
	Outputs between listed min and max are available.	Outputs between listed min and max are available. * 1000 lm/ft max. only for GZ, NW, WW and ASO.				

LENGTH (FT)	FINISH	VOLTAGE	DRIVER	CIRCUITS	MOUNTING/SUSPENSION	BATTERY (OPT)
4 4' 5 5' 6 6' 8 8' 12 12' S(L) System Run	W white BLK black* AP aluminum paint*	120 120 V 277 277 V 347 347 V UNV universal	DP dimming (0-10V) 1%	1 1 circuit 2 2 circuits + E(#) emergency circuit*	CA(#) drywall+cable length (36" std.) CT9(#) TB/TG 9/16+cable length (36" std.) CT15(#) TB/TG15/16+cable length (36" std.) CTS(#) screw slot+cable length (36" std.) SA(#) drywall+stem length >48" (18" std.) CASL(#) drywall cable sloped ceiling SASL(#) drywall stem sloped ceiling	B(#) battery pack (integral)
Available in 1' increments.	*Additional 5 working days required.			*Specify quantity	See Mounting kit guide for full specification code. White canopy standard	Minimum 5ft; Not available with 347V Please consult factory.

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.