



Refer to axislighting.com for complete fixture details, IES files, and installation instructions

Project _____

Type _____

Notes _____

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI

NOMINAL LUMEN OUTPUT	INPUT WATTS*	EFFICACY	SHIELDING
1100 lm/ft	8.8 W/ft	125 lm/W	SO
1100 lm/ft	9.1 W/ft	122 lm/W	BW
1000 lm/ft	9.3 W/ft	114 lm/W	GZ
1000 lm/ft	9.5 W/ft	112 lm/W	NW
1000 lm/ft	9.4 W/ft	113 lm/W	WW
1000 lm/ft	9.4 W/ft	113 lm/W	ASO

* Based on a 4 foot flush luminaire using one driver



Ordering Guide

TB3DLED									
PRODUCT ID		NOM. LUM/FT DOWN		CRI		COLOR TEMP.		SHIELDING	
TB3DLED	BEAM 3 - Pendant	300	300 lm/ft - min	80	80 CRI	30	3000 K	SO	spotless lens
	Direct LED	1000	1000 lm/ft - max for GZ, NW, WW, ASO.*			35	3500 K	ASO	Asymmetric
						40	4000 K	BW	Batwing
								NW	Narrow
		1100	1100 lm/ft - max					GZ	Graze
								WW	Wallwash