



Refer to axislighting.com for complete fixture details, IES files, and installation instructions

Project _____

Type _____

Notes _____

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI

NOMINAL LUMEN OUTPUT	INPUT WATTS*	EFFICACY	SHIELDING
1200 lm/ft	9.7 W/ft	124 lm/W	SO
1200 lm/ft	9.8 W/ft	122 lm/W	BW
1000 lm/ft	9.4 W/ft	144 lm/W	GZ
1000 lm/ft	9.8 W/ft	109 lm/W	NW
1000 lm/ft	9.5W/ft	111 lm/W	WW
1000 lm/ft	9.5W/ft	111 lm/W	ASO

* Based on a 4 foot flush luminaire using one driver

● DLC Approved Options

LUMEN OUTPUT	CRI	COLOR TEMP.	SHIELDING	LENGTH	VOLTAGE	DRIVER
400 lm/ft	80	3000 K	SO	4'	universal	DP
600 lm/ft		3500 K		8'		
800 lm/ft		4000 K		12'		
1000 lm/ft						



* Check the latest update on the DLC website for complete information. Not all versions may be DLC qualified.



Ordering Guide

TB3SLED									
PRODUCT ID		NOM. LUM/FT DOWN		CRI		COLOR TEMP.		SHIELDING	
TB4SLED	BEAM 4 - Surface LED	400	400 lm/ft - Minimum	80	80 CRI	30	3000 K	SO	spotless lens
		1000	1000 lm/ft - max for GZ, NW, WW, ASO.*			35	3500 K	ASO	Asymmetric
								BW	Batwing
		1200	1200 lm/ft - Maximum			40	4000 K	NW	Narrow
								GZ	Graze
								WW	Wallwash
		Outputs between listed min and max are available. * 1000 lm/ft max. only for GZ, NW, WW and ASO.				*Lens options use spotless lens. Choose only one of the options above.		Available in 1' increments.	
								* Additional 5 working days required.	

VOLTAGE	DRIVER	CIRCUITS	MOUNTING	BATTERY (OPTIONAL)
120 120 V	DP dimming (0-10V) 1%	1 1 circuit	SB9 surface TB/TG 9/16	B(##) battery pack (integral)
277 277 V		2 2 circuits	SB15 surface TB/TG 15/16	
347 347 V		+E(##) emergency circuit*	SBS surface screw slot t-bar	
UNV universal			S surface drywall ceiling	
			SC surface solid ceiling	
		*Specify quantity	Minimum 5ft; Not available with 347V Please consult factory	

❗ Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.