



Refer to axislighting.com for complete fixture details, IES files, and installation instructions

Project _____

Type _____

Notes _____

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI

NOMINAL LUMEN OUTPUT	INPUT WATTS*	EFFICACY	SHIELDING
1200 lm/ft	9.7 W/ft	124 lm/W	SO
1000 lm/ft	9.4 W/ft	144 lm/W	GZ
1000 lm/ft	9.8 W/ft	109 lm/W	NW
1000 lm/ft	9.5 W/ft	111 lm/W	ASO

* Based on a 4 foot flush luminaire using one driver

● DLC Approved Options

LUMEN OUTPUT	CRI	COLOR TEMP.	SHIELDING	LENGTH	VOLTAGE	DRIVER
400 lm/ft	80	3000 K	SO	4'	universal	DP
600 lm/ft		3500 K		8'		
800 lm/ft		4000 K		12'		
1000 lm/ft						



* Check the latest update on the DLC website for complete information. Not all versions may be DLC qualified.



Ordering Guide

TB4WDLED													
PRODUCT ID		NOM. LUM/FT DOWN		CRI		COLOR TEMP.		SHIELDING		LENGTH (FT)		FINISH	
TB4WDLED	Beam4 - Wall Direct LED	400	400 lm/ft - Minimum	80	80 CRI	30	3000 K	SO	spotless lens	4	4'	W	white
		1000	1000 lm/ft - max for GZ, NW, ASO.*			35	3500 K	ASO	Asymmetric	5	5'	BLK	black*
						40	4000 K	NW	Narrow	8	8'	AP	aluminum paint*
		1200	1200 lm/ft - Maximum					GZ	Graze	12	12'		
										S(L) System Run			
		Outputs between listed min and max are available. * 1000 lm/ft max. only for GZ, NW and ASO.						Choose only one of the options above.		Available in 1' increments.		* Additional 5 working days required.	

VOLTAGE		DRIVER		CIRCUITS		BATTERY (OPT.)	
120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	B(#)	battery pack (integral)
277	277 V			2	2 circuits		
347	347 V			+E(#) emergency circuit*			
UNV	universal						
			*Specify quantity			Minimum 5ft; Not available with 347V Please consult factory	

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.