



Refer to axislighting.com for complete fixture details, IES files, and installation instructions

Project _____

Type _____

Notes _____

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI

NOMINAL LUMEN OUTPUT	INPUT WATTS*	EFFICACY	SHIELDING
1200 lm/ft	9.7 W/ft	124 lm/W	FL
1200 lm/ft	9.7 W/ft	124 lm/W	RG
1200 lm/ft	9.8 W/ft	122 lm/W	BW
1000 lm/ft	9.8 W/ft	109 lm/W	NW
1000 lm/ft	9.5W/ft	111 lm/W	ASO
1000 lm/ft	9.4 W/ft	144 lm/W	GZ
1000 lm/ft	9.5W/ft	111 lm/W	WW

* Based on a 4 foot flush luminaire using one driver

● DLC Approved Options

LUMEN OUTPUT	CRI	COLOR TEMP.	SHIELDING	LENGTH	VOLTAGE	DRIVER
400 lm/ft	80	3000 K	FL	4'	universal	DP
600 lm/ft		3500 K		8'		
800 lm/ft		4000 K		12'		
1000 lm/ft						



* Check the latest update on the DLC website for complete information. Not all versions may be DLC qualified.



cULus Listed Type I.C.



Ordering Guide

BBRLED						
PRODUCT ID	NOM. LUM/FT DOWN	CRI	COLOR TEMP.	SHIELDING	LENGTH (FT)	FINISH
BBRLED Recessed LED	400 400 lm/ft - Minimum	80 80 CRI	30 3000 K	FL flush*	4 4'	W white
	1000 1000 lm/ft - max for GZ, NW, WW, ASO.*		35 3500 K	RG regressed*	5 5'	BLK black*
			40 4000 K	ASO asymmetric, flush only	6 6'	AP aluminum paint*
	1200 1200 lm/ft - Maximum			BW batwing, flush only	8 8'	
				NW narrow, flush only	12 12'	
				GZ graze, flush only	S(L) System Run	
				WW wallwash, flush only		
Outputs between listed min and max are available. * 1000 lm/ft max. only for GZ, NW, WW and ASO.				*Lens options use spotless lens. Choose only one of the options above.	Available in 1' increments.	* Additional 5 working days required.

VOLTAGE	DRIVER	CIRCUITS	MOUNTING	BATTERY (OPTIONAL)	OTHER (OPTIONAL)	QS
120 120 V	DP dimming (0-10V) 1%	1 1 circuit	TB9 t-bar 9/16"	B(##) battery pack 4' sections	EF end feed	QUICKSHIP +
277 277 V		2 2 circuits	TB15 t-bar 15/16"		FW flex whip (6' std)*	
347 347 V		+ E(##) emergency circuit*	ST screw slot t-bar		CP Chicago plenum	
UNV universal			TG9 tegular 9/16"		HD hold-down clip**	
			TG15 tegular 15/16"			
			DF drywall flange			
			D drywall flangeless			
			DB slip-through bracket			
			DS drywall spackle flange			
			TX tx Hunter Douglas techstyle*			
		*Specify quantity	*TX available with flush lens only	Minimum 5ft. Not available with 347V Please consult factory	*Other lengths available; please consult factory. **Only available for t-bar mounting	

❗ Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.