



Refer to axislighting.com for complete fixture details, IES files, and installation instructions

Project _____

Type _____

Notes _____

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI

NOMINAL LUMEN OUTPUT		INPUT WATTS*	EFFICACY	SHIELDING I/D
UPLIGHT	DOWNLIGHT			
1200 lm/ft	1200 lm/ft	18.1 W/ft	132 lm/W	SO/SO
1200 lm/ft	1000 lm/ft	17.9 W/ft	126 lm/W	SO/ASO
1200 lm/ft	1200 lm/ft	18.3 W/ft	132 lm/W	SO/BW
1200 lm/ft	1000 lm/ft	18.2 W/ft	124 lm/W	SO/NW
1200 lm/ft	1000 lm/ft	17.8 W/ft	127 lm/W	SO/GZ
1200 lm/ft	1000 lm/ft	17.9 W/ft	126 lm/W	SO/WW
1200 lm/ft	1200 lm/ft	17.7 W/ft	136 lm/W	BW/SO
1200 lm/ft	1000 lm/ft	17.5 W/ft	129 lm/W	BW/ASO
1200 lm/ft	1200 lm/ft	17.8 W/ft	135 lm/W	BW/BW
1200 lm/ft	1000 lm/ft	17.8 W/ft	127 lm/W	BW/NW
1200 lm/ft	1000 lm/ft	17.4 W/ft	130 lm/W	BW/GZ
1200 lm/ft	1000 lm/ft	17.5 W/ft	129 lm/W	BW/WW

* Based on a 4 foot flush luminaire using one driver



* Check the latest update on the DLC website for complete information. Not all versions may be DLC qualified.



Ordering Guide

TB4DILED													
PRODUCT ID		NOM. LUM/FT UP		NOM. LUM/FT DOWN		CRI		COLOR TEMP.		SHIELDING INDIRECT		SHIELDING DIRECT	
TB4DILED	BEAM4 - Pendant	400	400 lm/ft - Min.	400	400 lm/ft - Min.	80	80 CRI	30	3000 K	SO	spotless lens	SO	spotless lens
	Direct/Indirect LED	1200	1200 lm/ft - Max.	1000	1000 lm/ft - Max for GZ, NW, WW, ASO.*			35	3500 K	BW	batwing	ASO	Asymmetric
								40	4000 K			BW	Batwing
												NW	Narrow
												GZ	Graze
												WW	Wallwash
		Outputs between listed min and max are available.		Outputs between listed min and max are available. * 1000 lm/ft max. only for GZ, NW,WW and ASO.									

LENGTH (FT)	FINISH	VOLTAGE	DRIVER	CIRCUITS	MOUNTING/SUSPENSION	BATTERY (OPTIONAL)
4 4'	W white	120 120 V	DP dimming (0-10V) 1%	1 1 circuit	CA(#) drywall+cable length (36" std.)	B(#) battery pack (integral)
5 5'	BLK black*	277 277 V		2 2 circuits	CT9(#) TB/TG 9/16+cable length (36" std.)	
6 6'	AP aluminum paint*	347 347 V		+E(#) emergency circuit*	CT15(#) TB/TG15/16+cable length (36" std.)	
8 8'		UNV universal			CTS(#) screw slot+cable length (36" std.)	
12 12'					SA(#) drywall+stem length >48" (18" std.)	
S(L) System Run					CASL(#) drywall cable sloped ceiling	
					SASL(#) drywall stem sloped ceiling	
Available in 1' increments.	*Additional 5 working days required.			*Specify quantity	See Mounting kit guide for full specification code. White canopy standard	Minimum 5ft; Not available with 347V Please consult factory.

● DLC Approved Options

OUTPUT / UP	OUTPUT / DN	CRI	COLOR TEMP.	SHIELDING	LENGTH	VOLTAGE	DRIVER
750 lm/ft	500 lm/ft	80	3000 K 3500 K 4000 K	SO	4' 8' 12'	universal	DP

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.